




Position	Count	Description	Unit price
	-1	<p>22 SQE10-190</p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 96160200 3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.</p> <p>The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.</p> <p>The motor is a one-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range. The motor is fitted with a replaceable cable plug.</p> <p>Liquid: Maximum liquid temperature: 95 °F Max liquid temperature at 0.15 m/sec: 95 °F Density: 62.4 lb/ft³</p> <p>Technical: Speed for pump data: 10700 rpm Rated flow: 22 US gpm Rated head: 187 ft Approvals on nameplate: UL, cUL Approvals on motor nameplate: CE,UL,CUL</p> <p>Materials: Pump: Polyethylene / Stainless steel DIN W.-Nr. 1.4301 Motor: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: NPT 1 1/2 Minimum borehole diameter: 2.99 in</p>	On request

Position	Count	Description	Unit price
		<p>Electrical data:</p> <p>Motor type: MSE3</p> <p>Power input - P1: 2.32 kW</p> <p>Rated power - P2: 2.25 HP</p> <p>Main frequency: 60 Hz</p> <p>Rated voltage: 1 x 200-240 V</p> <p>Start. method: direct-on-line</p> <p>Service factor: 2,25</p> <p>Rated current: 11.2 A</p> <p>Power factor: 1,00</p> <p>Rated speed: 10700 rpm</p> <p>Enclosure class (IEC 34-5): 58</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 4.92 ft</p>	