



BATH VENTILATION SOLUTIONS



PRODUCT CATALOG

IMPROVING INDOOR AIR QUALITY THROUGH BETTER VENTILATION

www.fantech.net

Designing a Luxury Bath



You've spent hours pouring over magazines to find the perfect design for your new spa-like bathroom retreat. You've chosen the perfect tile, the whirlpool tub, beautiful faucets and luxurious shower sprays.

Don't stop there. Insist on a Fantech ultra-quiet Premium Bath Fan or Fan with Light to protect your new dream bath from the harmful effects of moisture, steam and odors.



It's powerful ventilation that you can live with.

Look for the Energy Star Symbol ...

Fantech is proud to partner with Energy Star to provide energy efficient bath ventilation products for your home. In fact, more than two-thirds of Fantech Premium Bath Fans exceed the minimum standards required for Energy Star Qualified products.



Energy Star Ventilation Fans Must Have:

- Super Quiet Operation
- High CFM/Watt Motor Efficacy (100 CFM Fan: 2.8 CFM/Watt)
- May Qualify For Local Utility Rebate

See QuickView Selection Guide (pgs. 8 & 9) to easily identify models that carry the Energy Star symbol.

The Ultimate in Design Flexibility plus Quiet Operation!

Don't let the roar of a noisy bath fan disrupt your peace and quiet. Choose an ultra-quiet, energy efficient Fantech Premium Bath Fan to protect your bath from the damaging effects of mold and mildew.

A New Level of Flexibility

Unlike standard exhaust fans, the motor of a Fantech fan mounts in a location away from the living area such as an attic. Small unobtrusive Ceiling Grilles, with or without lights, can be mounted in multiple locations over the shower, the toilet and/or the tub then ducted to the remote fan to quickly and efficiently whisk away moisture, steam and odors. One fan can also be used to ventilate two bath-to-back baths.



**Vent Only
Ceiling Grille**



**Ceiling Grille
with Dimmable
Halogen Light**



**Ceiling Grille with
Energy Star Compact
Fluorescent Light**

New Improved Ceiling Grille Housing Simplifies Installation

- Improved Airtight Design
- Longer Quick-Connect Duct Collar
- Hanger Bars Extend to 24" OC*
- Set Screw Locks Hanger Bars in Position
- Key Hole Mounting Slots
- UL "Wet Location" Rating
- IC "Insulation Contact" Rating

* PB190, PB360, PBV6 hanger bars extend to 16" OC.




**SEVEN
YEAR
WARRANTY**



All models are UL Listed for use in wet locations.
HVI (Home Ventilating Institute) certified for performance.
All models are IC Rated.

Fantech's Popular Inline Fan Powers Our Premium Bath Fans



- External rotor motor by ebm-papst
- Superior CFM at higher static pressure; 100 CFM @ .2 static
- 100% speed controllable
- Rated for continuous duty
- 4" to 8" Duct

Bath Fans & Fans with Lights – Single Grilles

Clear the air in smaller baths and powder rooms with the help of a Fantech Premium Bath Fan or Bath Fan with Light.

A small-scale grille mounts in the ceiling while the fan motor mounts in a remote location away from the living area. The result is quiet yet powerful ventilation that is sure to protect your home from the damaging effects of moisture, steam and mold.

**SEVEN
YEAR
WARRANTY**

FAN SIZING FOR BATHS UNDER 100 SQ. FT.

According to the guidelines of HVI (Home Ventilating Institute) baths 100 square feet or smaller require one CFM per square foot of bathroom*. To find the square footage simply multiply the length of the bath by the width.

EXAMPLE


7' x 9' bath = 63 sq. ft.

**7' x 9' = 63 sq. ft.
63 CFM Fan**

YOU WILL NEED A 63 CFM FAN

* Minimum 50 CFM

NOTE: For proper airflow in typical installations (when duct losses aren't calculated), use the 0.4"Ps (static pressure) rating point for correct fan selection.





PB100 Bath Fan

100 CFM fan, one Ceiling Grille and grille housing with damper. Uses 4" duct. Energy Star Qualified.

PB190 Premium Bath Fan (not shown)

190 CFM fan, one Ceiling Grille, and grille housing with damper. Uses 6" duct. Grille housing fits between 2 x 8 construction. Energy Star Qualified.



7" Diameter Ceiling Grille with Halogen Light
Dimmable for Night Light Setting



UL Listed for Wet Locations



PB100F Bath Fan with Fluorescent Light

100 CFM bath fan, one Ceiling Grille with Light, grille housing with damper, and 14-watt, instant-on, fluorescent bulb. Uses 4" duct. Energy Star Qualified. UL Listed for wet locations.



UL Listed for Wet Locations



PB100H Bath Fan with Dimmable Halogen Light

100 CFM bath fan, one Ceiling Grille with Light, grille housing with damper, and 50-watt halogen bulb. Uses 4" duct. UL Listed for wet locations.



UL Listed for Wet Locations

Contractor Friendly Installation

Fantech Premium Bath Fans are "flex duct friendly" making installation fast and easy. We recommend:

1. Use insulated flexible duct.
(Insulated flex duct allows sound from the fan to dissipate gradually so that it can not be heard in the bathroom.)
2. Ideally you should have at least 8 feet of flex duct between ceiling grilles and fan.
3. If applicable, use multiple ceiling grilles or ceiling grilles with lights.



Did You Know??

For Improved Indoor Air Quality, HVI (Home Ventilating Institute) recommends that the bath fan be left on for 20-minutes after the use of the bathroom.

ASHRAE (American Society of Heating, Refrigerating and Air Conditioning Engineers) recommends that controls be installed on bath fans for low level continuous or intermittent ventilation.

Ventech Programmable Controls can do all that and more! (See page 10 for complete description.)



Bath Fans & Fans with Lights – Dual Grilles

As the trend to larger spa-like bathrooms continues to gain in popularity, the need for proper ventilation becomes more important.

Gone are the days of a single bath fan in the center of the room. The key to proper ventilation in oversized baths filled with luxurious amenities is true spot ventilation at the source.

Quick removal of moisture at the source will keep your beautiful bath free of mold and the effects of extreme moisture.

Fantech has developed its Premium Bath Fans so that one remote mounted fan motor can effectively ventilate several areas of the bath.

Ceiling Grilles or Ceiling Grilles with Lights can be easily positioned over showers, whirlpool tubs, steam showers, toilet and vanity.

**SEVEN
YEAR
WARRANTY**

FAN SIZING FOR BATHS OVER 100 SQ. FT.

Ventilation for baths over 100 square feet is calculated based on the fixtures in the bath. Allow 50 CFM for each standard toilet, shower or tub. Whirlpool and jetted tubs are calculated at 100 CFM. Add up the CFMs for all fixtures and you'll have the total CFMs required.

EXAMPLE


11' x 14' Bath = 154 square feet

1 Toilet + 1 Shower + 1 Jetted Tub = 200 CFM

1 Toilet	50 CFM
1 Shower	50 CFM
1 Jetted Tub	100 CFM
Total	200 CFM

YOU WILL NEED A 200 CFM FAN.

**1 Toilet + 1 Shower +
1 Jetted Tub = 200 CFM**



NOTE: Fantech recommends that steam showers use a separate fan on a timer so that the fan may be shut off during shower use and then run afterward to dry the shower stall.




PB230-2 Premium Bath Fan with Dual Grilles

230 CFM fan, two Ceiling Grilles, two grille housings with dampers and Y-adapter (4x4x6). Uses 4" and 6" duct. Energy Star Qualified.




Premium Bath Fans – Dual Grille Models (Vent Only)



PB360-2 Larger Premium Bath Fan with Dual Grilles

360 CFM fan, two Ceiling Grilles, two grille housings with dampers and Y adapter (6x6x8). Uses 6" and 8" duct. Grille housing fits between 2 x 8 construction. Energy Star Qualified.

Multiple Bath Application



Premium Bath Fans with Lights – Dual Grille Models



PB230F-2 Premium Bath Fan – Dual Grilles with Fluorescent Lights

230 CFM fan, two Ceiling Grilles with Lights, two grille housings with dampers, two 14 watt instant-on Fluorescent bulbs and Y adapter (4x4x6). Uses 4" and 6" duct. Energy Star Qualified. UL Listed for wet locations.



PB230H-2 Premium Bath Fan – Dual Grilles with Dimmable Halogen Lights

230 CFM fan, two Ceiling Grilles with Lights, two grille housings with dampers, two 50 watt Halogen bulbs and Y-adapter (4x4x6). Uses 4" and 6" duct. UL Listed for wet locations.

Combination Bath Fans – Dual Grilles



Fantech takes the work out of choosing the right bath fan for your new home or remodeling project.

Premium Bath Combination Units.

Combo units include one exhaust fan, one lit and one unlit Ceiling Grille. A single model number provides the exact bath fan components to install an effective two-location exhaust system.

Want to add an additional exhaust location? Just choose an additional Ceiling Grille with or without a light to turn your one or two location bath fan into a fabulous multiport system.



UL Listed for
Wet Locations

**SEVEN
YEAR
WARRANTY**

Combination Units - Dual Grilles - One Vent & Light / One Vent-Only



UL Listed for
Wet Locations



PB230FV-2 Fan with One Ceiling Grille with Fluorescent Light and One Vent-Only Ceiling Grille

230 CFM fan, one Ceiling Grille with Light, one Vent-Only Ceiling Grille, two grille housings with dampers, one 14 watt instant-on Fluorescent bulb and Y adapter (4x4x6). Uses 4" and 6" duct. Energy Star Qualified. UL Listed for wet locations.



UL Listed for
Wet Locations



PB230HV-2 Fan with One Ceiling Grille with Dimmable Halogen Light and One Vent-Only Ceiling Grille

230 CFM fan, one Ceiling Grille with Light, One Vent-Only Ceiling Grille, two grille housings with dampers, one 50 watt Halogen bulb and Y adapter (4x4x6). Uses 4" and 6" duct. Energy Star Qualified. UL Listed for wet locations.

Exterior Mount Bath Fans & Expansion Grilles

Fantech has expanded its Premium Bath Fan selection to include a trio of models powered by exterior mounted wall fans. An excellent alternative when space is an issue or direct venting to the outside is required. Ideal for homes, condominiums and apartment complexes. Choose vent only or lighted models.

**SEVEN
YEAR
WARRANTY**



PBW110H Exterior Wall Mount Bath Fan with Dimmable Halogen Light
120 CFM fan, one Ceiling Grille with Light, grille housing with damper and 50 watt halogen bulb. UL Listed for wet locations.



UL Listed for Wet Locations



Exterior Mount Bath Fans




PBW110 Exterior Wall Mount Bath Fan
120 CFM fan, one Ceiling Grille and grille housing with damper. Energy Star Qualified.



PBW110F Exterior Wall Mount Bath Fan with Fluorescent Light
120 CFM fan, one Ceiling Grille, one grille housing with damper and one 14-watt instant-on fluorescent bulb. UL Listed for wet locations. Energy Star Qualified.

UL Listed for Wet Locations

Ideal for First Floor Baths



Expansion Grilles with Housings



UL Listed for Wet Locations

PBF4 Ceiling Grille with Fluorescent Light
For use with Fantech remote fans. Includes Ceiling Grille with Fluorescent light, grille housing with damper, four hanger bars and 14-watt instant-on fluorescent bulb. Grille housing: 7³/₁₆"L x 7³/₁₆"W x 5⁵/₁₆"H. Fits between 2x6 construction.



UL Listed for Wet Locations

PBH4 Ceiling Grille with Dimmable Halogen Light
For use with Fantech remote fans. Includes Ceiling Grille with Halogen light, grille housing with damper, four hanger bars and 50-watt halogen bulb. Grille housing: 7³/₁₆"L x 7³/₁₆"W x 5⁵/₁₆"H. Fits between 2x6 construction.



PBV4 Ceiling Grille
For use with Fantech remote fans. Includes Ceiling Grille, grille housing with damper and four hanger bars. Grille housing: 7³/₁₆"L x 7³/₁₆"W x 5⁵/₁₆"H. Fits between 2x6 construction.



PBV6 Ceiling Grille
For use with Fantech remote fans. Includes Ceiling Grille, grille housing with damper and four hanger bars. Grille housing: 8"L x 8"W x 7¹/₈"H. Fits between 2x8 construction.

Quick View Selection Guide

Fantech Premium Bath Fan Model Number	CFM @ .2 Static Pressure	CFM @ .4 Static Pressure	Duct Size	Watts @ .2 Static Pressure		Lamp	SEVEN YEAR WARRANTY
PREMIUM BATH FANS							
PB100 	100	78	4"	19	Yes	—	Yes
PB190 	190	162	6"	61	Yes	—	Yes
PREMIUM BATH FANS - DUAL GRILLES							
PB230-2 	230	198	4"/6"	71	Yes	—	Yes
PB360-2 	360	308	6"/8"	122	Yes	—	Yes
PREMIUM BATH FANS WITH LIGHTS							
PB100F 	100	78	4"	19	Yes	14 Watt Instant-on Compact Fluorescent (PBB14)*	Yes
PB100H 	100	78	4"	19	—	50 Watt Halogen (PBB50)	Yes
PREMIUM BATH FANS WITH LIGHTS - DUAL GRILLES							
PB230F-2 	230	198	4"/6"	71	Yes	14 Watt Instant-on Compact Fluorescent (PBB14)*	Yes
PB230H-2 	230	198	4"/6"	71	—	50 Watt Halogen (PBB50)	Yes
PREMIUM BATH FANS - COMBINATION UNITS - ONE LIT AND ONE UNLIT GRILLE							
PB230FV-2 	230	198	4"/6"	71	Yes	14 Watt Instant-on Compact Fluorescent (PBB14)*	Yes
PB230HV-2 	230	198	4"/6"	71	—	50 Watt Halogen (PBB50)	Yes



*The Compact Fluorescent bulb used in Fantech Premium Bath Fans has a color temperature of 2733 Kelvin and CRI of 81. Average bulb life: 10,000 hours. Need replacement bulbs? Order PBB14 for Fluorescent Models; PBB50 for Halogen Models.

Fantech Premium Bath Fan Model Number	CFM @ .1 Static Pressure	CFM @ .2 Static Pressure	Duct Size	Watts @ .2 Static Pressure	ENERGY STAR	Lamp	SEVEN YEAR WARRANTY
EXTERIOR WALL MOUNT FANS AND FANS WITH LIGHTS							
PBW110 	120	112	4"	19	Yes	—	Yes
PBW110F 	120	112	4"	19	Yes	14 Watt Instant-on Compact Fluorescent (PBB14)*	Yes
PBW110H 	120	112	4"	19	—	50 Watt Halogen (PBB50)	Yes

*The Compact Fluorescent bulb used in Fantech Premium Bath Fans has a color temperature of 2733 Kelvin and CRI of 81. Average bulb life: 10,000 hours. Need replacement bulbs? Order PBB14 for Fluorescent Models; PBB50 for Halogen Models.

Fantech Premium Bath Fan Model Number	Duct Size	Housing Dimensions	Lamp	SEVEN YEAR WARRANTY
EXPANSION GRILLES WITH HOUSINGS AND DAMPERS				
PBF4 	4"	7 ³ / ₁₆ "L x 7 ³ / ₁₆ "W x 5 ⁵ / ₁₆ "H	14 Watt Instant-on Compact Fluorescent (PBB14)*	Yes
PBH4 	4"	7 ³ / ₁₆ "L x 7 ³ / ₁₆ "W x 5 ⁵ / ₁₆ "H	50 Watt Halogen (PBB50)	Yes
PBV4 	4"	7 ³ / ₁₆ "L x 7 ³ / ₁₆ "W x 5 ⁵ / ₁₆ "H	—	Yes
PBV6 	6"	8"L x 8"W x 7 ¹ / ₈ "H	—	Yes

* The Compact Fluorescent bulb used in Fantech Premium Bath Fans has a color temperature of 2733 Kelvin and CRI of 81. Average bulb life: 10,000 hours. Need replacement bulbs? Order PBB14 for Fluorescent Models; PBB50 for Halogen Models.



Adding an additional ceiling grille to your installation? Don't forget to order an extra Y-adapter.

FY Series
Five different models to choose from: 4x4x4"; 6x6x6"; 6x6x4"; 6x4x4"; 8x6x6".

Fantech Recommends the Use of Insulated Flex Duct with Fantech Premium Bath Fans



FAN DIMENSIONS

Fantech Premium Bath Fan Model Number	Width (Diameter)	Height
PB100	9 ¹ / ₂ "	9 ⁵ / ₈ "
PB230	11 ³ / ₄ "	9 ⁵ / ₈ "
PB360	13 ¹ / ₄ "	12 ¹ / ₄ "
PBVV	10 ¹ / ₄ "	13"



Programmable Controls for Improved Home Ventilation

For ultimate control of your single or dual grille Fantech Premium Bath Fans install one Ventech Master Control (VT20M) and one or more Auxiliary Controls (VT20A). With just a touch of a button in any location, the fan will run for 20 minutes. Simple slide controls on the side of the Master Control allow for customized operation of the fan for intermittent or continuous low-level ventilation.

It's the easiest, most cost-effective way to improve indoor air quality in the homes you build, buy or remodel.

Meets the recommendations of US and Canadian building codes, utility programs, HVI and ASHRAE Standard 62.2.

VT20M

Ventech Main Control

Main Control features easy-set slide adjustment for fan speed and run-time per hour. Controls are hidden behind cover plate. Use with up to three Auxiliary Controls (VT20A) to allow 20 minute high speed boost in up to four locations. 120V, 60 Hz. Max. Load 2.5 amps.



Set Timer Here

Set Speed Control Here



MEETS ASHRAE
STANDARD 62.2



VT20A

Ventech Auxiliary Control


Low voltage wire connects Auxiliary Control to Main Control for 20 minute high speed boost in secondary location. Use up to 3 with Main Control.



FD60EM

Electronic Timer Control

10, 20, 30, 60 minute timer. Decora style switch plate. 115V/20A



SCD5

Slide Speed Control

Decora style slide control with on/off. 115V/5A



PBB14

Replacement Bulbs

14-watt compact fluorescent bulb for use in Fantech Premium Bath Fans.



PBB50

Replacement Bulbs

50-watt halogen bulb for use in Fantech Premium Bath Fans.

For additional information on items shown above, visit www.fantech.net.



United States

1712 Northgate Blvd.
Sarasota, FL 34234
800-747-1762; 941-309-6000
Fax: 800-487-9915; 941-309-6099
www.fantech.net; info@fantech.net

Canada

50 Kanalfakt Way
Bouctouche, NB E4S 3M5
800-565-3548; 506-743-9500
Fax: 877-747-8116; 506-743-9600
www.fantech.ca; info@fantech.ca

Fantech, reserves the right to modify, at any time and without notice, any or all of its products' features, designs, components and specifications to maintain their technological leadership position.

Item#412220 SBB1107

©2007 Fantech, Inc. All Rights Reserved.

Distributed locally by: