

# Heavy Duty Floats

## Copper Floats



High grade copper construction.  
Firmly bonded overlapping joints (leadfree solder).

**Maximum Temperature - 200°F**

Diameter Size	Model	Thread Connection	Inner Pack	Master Pack	Weight each (oz.)
4" x 5"	CX	1/4-20	1	8	2.6
4"	C4	1/4-20	1	8	4.3
5"	C5	1/4-20	1	12	6.5
6"	C6	1/4-20	1	8	8.3
6"	C6-7	5/16-18	1	8	8.3
6"	C6-3	3/8-16	1	24	8.3
7"	C7	5/16-18	1	12	15.3
8"	C8	3/8-16	1	8	20.0
10"	C10	3/8-16	1	4	44.0
12"	C12	3/8-16	1	4	67.0

## Plastic Floats



Non-electrolytic, highly corrosion resistant. Unaffected by salts and caustic fluids. All injection molded Polyethylene construction. Resistant to sunlight deterioration.

**Maximum Temperature - 140°F**

Diameter Size	Model	Inner Pack	Master Pack	Weight each (oz.)
4" x 5"	PX	1	10	2.3
6"	P6	1	10	7.3
6"	P6-7	1	10	7.3
8"	P8	1	10	12.6
8"	P8-7	1	10	12.6
8"	P8-1	1	10	12.6
2 pcs. 6"	P12	1	1	14.6
2 pcs. 8"	P16	1	1	25.1

\* Assembly of two P6's.

\*\* Assembly of two P8's.

## Heavy Duty Float Valve Replacement Parts




**1MN**  
(Long Arm)

**2MN**  
(Short Arm)

### Valve Arms (Bronze)

For valve sizes 3/8", 1/2" and 3/4"

Model	Thread Size	Inner Pack	Master Pack
1MN	N/A	10	100
2MN-1	1/4-20	10	100
2MN-7	5/16-18	10	100
2MN-3	3/8-16	10	100
2MN-9	1/8	10	100



**1JB**  
(Long Arm)

**2JB**  
(Short Arm)

### Valve Arms (Bronze)

For valve sizes 1" through 2"

Model	Thread Size	Inner Pack	Master Pack
1JB	N/A	10	100
2JB-1	1/4-20	10	100
2JB-7	5/16-18	10	100
2JB-3	3/8-16	10	100
2JB-9	1/8 NPSF	10	100
2JB-4	1/4 NPSF	10	100