


FV441

HARVARD Four in One Plastic Foot Valve

- Positive sealing - spring loaded valve poppet closes against a smooth tapered seat.
- Corrosion resistant nylon body and internals.
- Self cleaning design for continuous positive sealing.
- Large screen designed to assure smooth water passage and better suction.
- Tapered screen eliminates pipe joint hang-ups during installation.
- Fits four pipe sizes., 3/4" through 1 1/2".
- **Third party certified to NSF/ANSI 372.**



LOW-LEAD



Part Number	Size	Ctn Qty
FV441	3/4" through 1 1/2"	100


FV Series

Brady Plastic Foot & Check Valve Features:

- "Nose Cone" diffuser reduces friction.
- 50% greater water flow.
- Acetal copolymer construction.
- Non-electrolytic, non-corrosive.
- Spring loaded, 316 stainless steel
- BUNA-N seal
- Pressure max: 175 psi
- Temperature max: 180 F
- LC check valve, FPT x FPT
- **Third party certified to NSF/ANSI 372.**


LC Series

Part Number	Size	Ctn Qty
-------------	------	---------

Brady Foot Valve - Spring Loaded

FV75	3/4"	125
FV100	1"	100
FV125	1-1/4"	50
FV150	1-1/2"	50

Brady Check Valve- Spring Loaded

LC75	3/4"	24
LC100	1"	24
LC125	1-1/4"	24
LC150	1-1/2"	12


FV SN Series

Brady Foot Valve Strainer

FV75SN	3/4"	50
FV100SN	1"	50
FV125SN	1-1/4"	50
FV150SN	1-1/2"	50