



Installation Instructions / Warranty





Starck
10452181



Montreux
16549181

AXOR[®]


hansgrohe




Starck 10406001

**Tube shown: Duravit
Philippe Starck
Starck X**

Freestanding tub with outside covering.



* If clearance is less than 1 1/8", order extension 97686000.




Technical Data

Operating pressure: max. 145 psi
Recommended operating pressure: 14.5 - 72 psi
Test pressure: 232 psi
Hot water temperature: max. 176° F*
Recommended hot water temperature: 120° F - 140° F*
1/2" NPT inlets

These tub fillers are not anti-scald. If required by local plumbing code, install remote pressure balance valve 13418181 to the hot and cold supplies within 6' of the rough.

*Please know and follow all applicable local plumbing codes when setting the temperature on the water heater.

Replacement Parts




Installation - 10452181

Use the rough as a template to mark the positions of the screw holes in the subfloor. Use an 8 mm bit to drill the holes.


Install the anchors (included).

Fasten the rough to the subfloor with the screws provided. Make sure that the rough is level.




Wrap the threads on the supplies with Teflon thread tape.

Install the supplies in the rough. For proper operation of the tub filler, the hot supply should be installed on the left, the cold supply on the right.




Remove the flush insert plug from the cold water side of the rough using a 17 mm wrench. Install a hose bibb and a hose. Turn on the water and allow the line to flush thoroughly.


Repeat the flushing procedure on the hot water side.



Replace and tighten the plugs (1). Pressure test the unit (2).




Install the plaster shield. Use a 5 mm Allen wrench to tighten the screws.



Install the flooring material. Please know and follow all applicable local codes regarding waterproofing.




The surface of the finished floor must fall somewhere between the "minimum" and "maximum" markings on the plaster shield.



Axor Montreux Free-standing Tub Filler Rough

16549181

This unit is for use with Axor Montreux free-standing tub filler 16547XX1.



Technical Data


| | |
|------------------------------------|------------------|
| Operating pressure: | max. 145 psi |
| Recommended operating pressure: | 14.5 - 72 psi |
| Test pressure: | 232 psi |
| Hot water temperature: | max. 176° F* |
| Recommended hot water temperature: | 120° F - 140° F* |

This tub filler is not anti-scald. If required by local plumbing code, install remote pressure balance valve 13418181 to the hot and cold supplies within 6' of the rough.

*Please know and follow all applicable local plumbing codes when setting the temperature on the water heater.


Replacement Parts

| | | |
|---|------------------|----------|
| 1 | mounting kit | 96260000 |
| 2 | flush insert | 96459000 |
| 3 | hex socket screw | 97670000 |



Installation - 16549181


Wrap the threads on the two plugs with Teflon thread tape. Install one plug on each rough.



Use the mounting plate as a template to mark the positions of the screw holes in the subfloor. Use an 8 mm bit to drill the holes.


Install the anchors (included).

Fasten the roughs to the subfloor with the screws provided. **Make sure that the roughs are level.**



Wrap the threads on the supplies with Teflon thread tape.

Install the supplies in the roughs. For proper operation of the tub filler, the hot supply should be on the left, the cold supply on the right.




Remove the flush insert plug from the cold water side of the rough. Install a hose bibb and a hose. Turn on the water and allow the line to flush thoroughly.


Repeat the flushing procedure on the hot water side.



Replace and tighten the plugs. Pressure test the unit.




Install the plaster shields. Use a 5 mm Allen wrench to tighten the screws.



Install the flooring material. Please know and follow all applicable local codes regarding waterproofing.

The surface of the finished floor must fall somewhere between the "minimum" and "maximum" markings on the plaster shield.



Cleaning Recommendation for Hansgrohe Products

Modern faucetry and shower products utilize a combination of materials to comply with the needs of the market with regard to design and functionality.

To avoid damage, it is necessary to use some caution when cleaning. Damage caused by improper treatment is not covered under the Hansgrohe warranty.

Cleaning Materials for Faucets and Showers

- To remove lime scale, use only products made specifically for that purpose. Always follow the manufacturer's instructions when using.
- Do not use cleaners that contain hydrochloric, formic, acetic, or phosphoric acids, as these will cause considerable damage to finishes and to plastic components.
- Never mix cleaning materials.
- Never use cleaners containing abrasives. Do not use abrasive cleaning cloths, pads, or sponges.

Cleaning Procedures

- Clean your faucets and shower products as and when required. Regular cleaning will prevent scale buildup and water spotting.
- Follow the label instructions. Do not allow any cleaner to remain on the product for longer than necessary.
- When using spray cleaners, spray first onto a sponge or cloth – do not spray directly onto the product.
- After cleaning, rinse thoroughly with clear water to remove any cleaner residue.

Important

- Soap and shampoo residue can also cause damage to the product. Rinse well with clean water after use.
- If the surface is already damaged, harsh cleaning materials will cause further damage.

Limited Lifetime Consumer Warranty

This product has been manufactured and tested to the highest quality standards by Hansgrohe, Inc. ("Hansgrohe"). This warranty is limited to Hansgrohe products which are purchased by a consumer in the United States after March 1, 1996, and installed in either the United States or Canada.

WHO IS COVERED BY THE WARRANTY

This warranty extends to the original consumer purchaser only.

WHAT IS COVERED BY THE WARRANTY

This warranty covers only your Hansgrohe manufactured product. Hansgrohe warrants this product against defects in material or workmanship as follows: Hansgrohe will repair at no charge for parts only or, at its option, replace any product or part of the product which proves defective because of improper workmanship and/or material, under normal installation, use, service and maintenance. If Hansgrohe is unable to provide a replacement and repair is not practical or cannot be timely made, Hansgrohe may elect to refund the purchase price in exchange for the return of the product.

LENGTH OF WARRANTY

Replacement or repaired parts of products will be covered for the term of this warranty as stated in the following two sentences. If you are a consumer who purchased the product for use primarily for personal, family, or household purposes, this warranty extends for as long as you own the product and the home in which the product is installed. If you purchased the product for use primarily for any other purpose, including, without limitation, a commercial purpose, this warranty extends only (i) for 1 year, with respect to Interaktiv and Retroaktiv products, and (ii) for 5 years, with respect to AXOR, ShowerPower and Pharo products.

THIS WARRANTY DOES NOT COVER, AND HANSGROHE WILL NOT PAY FOR:

- A. Conditions, malfunctions or damage not resulting from defects in material or workmanship.
- B. Conditions, malfunctions or damage resulting from (1) improper installation, improper maintenance, misuse, abuse, negligence, accident or alteration, or (2) the use of abrasive or caustic cleaning agents or "no rinse" cleaning products, or the use of the product in any manner contrary to the product instructions.
- C. Labor or other expenses for the disconnection or return of the product for warranty service, or for installation or reinstallation of the product.
- D. Accessories or related products not manufactured by Hansgrohe.

TO OBTAIN WARRANTY SERVICE

Contact your Hansgrohe retailer, or write to Technical Service at:

Hansgrohe Inc.
1492 Bluegrass Lakes Parkway
Alpharetta GA 30004

Or, call Hansgrohe toll-free at (800) 334-0455.

In requesting warranty service, you will need to provide

- 1. The sales receipt or other evidence of the date and place of purchase.
- 2. A description of the problem.
- 3. Delivery of the product or the defective part, postage prepaid and carefully packed and insured, to Hansgrohe Inc. 1492 Bluegrass Lakes Parkway, Alpharetta, Georgia 30004, Attention: Technical Service, if required by Hansgrohe.

When warranty service is completed, any repaired or replacement product or part will be returned to you postage prepaid.

EXCLUSIONS AND LIMITATIONS

REPAIR OR REPLACEMENT (OR, IN LIMITED CIRCUMSTANCES, REFUND OF THE PURCHASE PRICE) AS PROVIDED UNDER THIS WARRANTY IS THE EXCLUSIVE REMEDY OF THE PURCHASER. HANSGROHE NEITHER ASSUMES NOR AUTHORIZES ANY PERSON TO CREATE FOR IT ANY OBLIGATION OR LIABILITY IN CONNECTION WITH THIS PRODUCT.

HANSGROHE SHALL NOT BE LIABLE TO PURCHASER OR ANY PERSON FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES, ARISING OUT OF BREACH OF THIS WARRANTY OR ANY IMPLIED WARRANTY (INCLUDING MERCHANTABILITY).

Some States do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may have other rights which vary from State to State.

You may be required by law to give us a reasonable opportunity to correct or cure any failure to comply before you can bring any action in court against us under the Magnuson-Moss Warranty Act.

PRODUCT INSTRUCTIONS AND QUESTIONS

Upon purchase or prior to installation, please carefully inspect your Hansgrohe product for any damage or visible defect. Prior to installing, always carefully study the enclosed instructions on the proper installation and the care and maintenance of the product. If you have questions at any time about the use, installation, or performance of your Hansgrohe product, or this warranty, please call or write to us at the toll-free number and address printed above.

hansgrohe

Hansgrohe, Inc. • 1490 Bluegrass Lakes Parkway • Alpharetta, GA 30004
Tel. 770 360-9880 • Fax 770 360 9887

www.hansgrohe-USA.com