



REFRIGERANT

RECOVERY



SPECIFICATIONS

MODEL (LBS.)	30 POUND	50 POUND	123 POUND	239 POUND	1,000 POUND
HEIGHT (IN.)	17.7	18.8	54.8	48.7	57.3
HEIGHT (MM)	450.9	477.5	1,392	1,237	1,455
WATER CAPACITY (LBS)	26.2	47.7	123	239	1,000
WATER CAPACITY (KG)	11.9	21.7	55.6	108.4	450
NOMINAL TARE WEIGHT (LBS.)	17	27.8	58	78.5	334
NOMINAL TARE WEIGHT (KG)	7.7	12.6	26.3	35.6	151.5
CYLINDER DIAMETER (IN.)	9.1	12.3	10	14.7	30
CYLINDER DIAMETER (MM)	231.1	312.4	254	373.4	762
CYLINDER VOLUME (CU. IN.)	726	1,324	3,393	6,591	27,461
CYLINDER VOLUME (LITERS)	11.9	21.7	55.6	108	450
COLLAR DIAMETER (IN.)	6.5	6.5	3.9	11.4	16
COLLAR DIAMETER (MM)	165.1	165.1	98.4	289.6	406.4
COLLAR HEIGHT (IN.)	5.1	5.1	N/A	6.4	6.9
COLLAR HEIGHT (MM)	130	130	N/A	163	175
FOOTRING DIAMETER (IN.)	7.8	7.8	10	14.5	22
FOOTRING DIAMETER (MM)	198.1	198.1	254	368.3	558.8
STANDARD SPECIFICATION	DOT-4BA-400	DOT-4BA-400	DOT-4BW-400	DOT-4BW-260	DOT-4BW-260
SERVICE PRESSURE (PSIG)	400	400	400	260	260
SERVICE PRESSURE (BAR)	27.6	27.6	27.6	17.9	17.9
TEST PRESSURE (PSIG)	800	800	800	520	520
TEST PRESSURE (BAR)	55.2	55.2	55.2	35.9	35.9
OPTIONAL SPECIFICATION	N/A	N/A	N/A	N/A	DOT-4BW-400
SERVICE PRESSURE (PSIG)	N/A	N/A	N/A	N/A	400
SERVICE PRESSURE (BAR)	N/A	N/A	N/A	N/A	27.6
TEST PRESSURE (PSIG)	N/A	N/A	N/A	N/A	800
TEST PRESSURE (BAR)	N/A	N/A	N/A	N/A	55.2

All tare weights and dimensions are approximate.

To convert to refrigerant capacity:

Maximum allowable gross cylinder fill weight is 0.8 x water capacity x specific gravity of the refrigerant recovered @ 77°F/25°C + the cylinder tare weight.

Cylinder photos are not shown to scale.