



### Function

- Used as auxiliary connections through which the fire department can pump water to supplement existing water supplies
- Provides 250 GPM flow (maximum), per 2½" inlet

### Features/Components

- **Single** inlet connections incorporate a straight-thru, non-clappered design with female NPT outlets
- **Two and three-way** inlet connections feature brass bodies with integral drop-clapper inlets and female NPT outlets
- **Four-way square** and **four-way in-line** inlet connections feature brass bodies with female NPT inlets and outlets
- **Six-way** inlet connections feature steel bodies with integral drop-clapper inlets and female NPT outlets
- **Standard components, all connections:**  
Female hose thread swivel inlets (**models 6242/6264** with clapper-snoots), plugs with chains, 18" cover sleeve (**model 6202** with tube), and identification plate
- Cast brass construction\*, standard

\*Optional brass finishes, add suffix to model no.

-B Polished; -C Rough Chrome Plated; -D Polished Chrome Plated

### Single, Two, Three, Four, and Six-way Connections

Model No.	Size	Clappers	Overall Height	Radius of Body Swing
6204	1½" x 1½"	---	20"	4"
6214	2½" x 2½"	---	20"	4"
6224	4" x 2½" x 2½"	2	24"	6¾"
6226	6" x 2½" x 2½"	2	24"	7¼"
6236	6" x 2½" x 2½" x 2½"	3	24"	7"
6242	6" x 2½" square, 4-way	4	34"	7½"
6244	6" x 2½" in-line, 4-way	4	24"	12½"
6264*	8" x 2½" in-line, 6-way	6	26½"	19"


#### Identification Plate Lettering:

- AUTO SPKR
- AUTO SPKR & STANDPIPE
- STANDPIPE
- DRY STANDPIPE


\* Steel body painted black for cast brass & polished brass finish  
Steel body painted silver for rough chrome & polished chrome

### Notes


- Always specify hose threads and identification plate lettering
- Contact Guardian for current approvals and special requirements




6202/6214




6224/6226



6236



6242



6244/6264

\* 39" for 6-way