

Position	Count	Description	Unit price
	-1	<p>CR 1-13 A-FGJ-A-E-HQQE</p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 96082133 Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.</p> <p>The pump has the following characteristics:</p> <ul style="list-style-type: none"> - Impellers and intermediate chambers are made of Stainless steel DIN W.-Nr. DIN W.-Nr. 1.4301. - Pump head and base are made of Cast iron. - The shaft seal has assembly length according to DIN 24960. - Power transmission is via cast iron split coupling. - Pipework connection is via ANSI flanges. <p>The motor is a 3-phase AC motor.</p> <p>Liquid: Liquid temperature range: -4 .. 248 °F Density: 62.4 lb/ft³</p> <p>Technical: Speed for pump data: 3466 rpm Rated flow: 9.69 US gpm Rated head: 284 ft Shaft seal: HQQE Approvals on nameplate: ANSI/NSF61</p> <p>Materials: Pump housing: Cast iron EN-JL1030 ASTM 25 B Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p>	On request

Printed from Grundfos CAPS [2012.01.058]

96082133 CR 1-13 60 Hz

