




If you can **core through it**, QwikSeal can **connect to it**.


QwikSeal allows you to connect service pipe to solid wall, profile, closed profile and corrugated pipe.



Corrugated



SDR-35



Clay



Concrete & Manholes

Fernco QwikSeal

Part No.	Pipe Inlet	Pipe Size Application
QS-4	4" SDR-35	8" diameter and larger pipe
QS-4S40	4" SCH-40	8" diameter and larger pipe
QS-6	6" SDR-35	10" diameter and larger pipe
QS-6S40	6" SCH-40	10" diameter and larger pipe
QS-8	8" SDR-35	15" diameter and larger pipe

OTHERS

QwikSeal Advantages

Meets ASTM C 923	✓
When tested in Concrete Manholes:	✓
- Creates compression seal that is water tight up to 10 psi	✓
- Can handle up to 7 degrees of deflection	✓
Easy identification - Grey = Sch 40, Green = SDR-35	✓
Not dependant on the host pipe size, type or material	✓
Reduced complexity: 1 QwikSeal = Many Solutions	✓
Less inventory = More turns	✓

Fernco Hole Saws

Part No.	Description
QS-5x6HS	5" OD x 6" Deep Hole Saw with Arbor
QS-7x6HS	7" OD x 6" Deep Hole Saw with Arbor
QS-9x6HS	9" OD x 6" Deep Hole Saw with Arbor
QS-SAW5	5" OD x 6" Deep - HOLE SAW ONLY
QS-SAW7	7" OD x 6" Deep - HOLE SAW ONLY
QS-SAW9	9" OD x 6" Deep - HOLE SAW ONLY
QS-ARBOR	3/8" x 12" Drill with 1/2" Arbor
QS-ADAPTER	1 1/4" x 3/4" Coring Machine Adapter

Fernco Coring Bits

Part No.	Description
QS-5x14CB	5" OD x 14" Length Abrasive Coring Bit
QS-7x14CB	7" OD x 14" Length Abrasive Coring Bit
QS-9x14CB	9" OD x 14" Length Abrasive Coring Bit