### FIRE DEPARTMENT CONNECTIONS

### #231 Sidewalk Siamese

Sidewalk Siamese connections are available with 4" or 6" outlets with either 2 or 3, 21/2" or 3" swivel inlets. Standard is cast brass. Polished brass or polished chrome optional. The assembly comes complete with cast body, 18" sleeve, escutcheon plate and plugs. Threads to local fire department specifications. Specify "Auto Sprinkler" or "Standpipe" or combination plate when ordering.

#### #7209 Sidewalk Siamese

Square Sidewalk Siamese connections are available with 6" outlets with four 21/2" swivel inlets. Standard is cast brass. Polished brass or polished chrome optional. The assembly comes complete with cast body, 18" sleeve, escutcheon plate and plugs. Threads to local fire department specifications. Specify "Auto Sprinkler" or "Standpipe," or combination plate when ordering.



# **#690 Sidewalk Storz Fire Department** Connection

Similar to traditional sidewalk Siamese connections. These connections have one storz inlet, 4" or 5" by 4" or 6" NPT. Comes complete with 90° storz connection, cap, 18" sleeve, and escutcheon plate. Bright aluminum. Painted red or Polished Aluminum optional. Specify "Auto-Sprinkler" or "Standpipe," or combination plate when ordering.



### #7106P Single Fire Department Connection

7106P Brass Single Fire Department connection. Furnished with rectangular escutcheon, plug, and chain. Female inlet 2½". Lettered "Auto Sprinkler" or "Standpipe." Threads to local fire department specifications. Finish: cast brass. Polished brass or chrome plated optional. Specify size: 2½" x 2½" or 3" x 2½".



### **#7106R Single Fire Department Connection**

7106R Brass Single Fire Department connection. Furnished with round escutcheon, plug and chain. Female inlet 21/2". Lettered "Auto Sprinkler" or "Standpipe." Threads to local fire department specifications. Finish: cast brass. Polished brass or chrome plated optional. Specify size: 2½" x 2½" or 3" x 2½".



## #276 Flush Type Fire Department Connection

Moon flush type fire department connections are designed for installation where space will not accommodate a projecting unit. The individual drop clappers valves are included, together



with plugs, chains and escutcheon plate lettered "Auto Sprinkler" or "Standpipe." Siamese body is roughed-in during construction: escutcheon and nipple assemblies are installed after construction. Pipe nipples by others. Finish: cast brass. Optional: Polished brass or chrome plated. Threads: to local fire department specifications. Specify: Straight, 90° angle or inverted angle body.

### #270 Projecting Siamese

Projecting fire department connections are available in 4" and 6" outlets with 2%" or 3" swivel inlets. Two individual drop clapper valves are included, together with plugs, chains, and escutcheon plate lettered "Auto Sprinkler or Standpipe." Threads to local fire department



specifications. Finish: cast brass. Polished brass or chrome plated optional.

### #2112 Straight Ball Drip

Fire regulations in most cities require automatic ball drip be placed between the inside check valve and the Siamese. Available in 1/2" or 34". Brass construction.



