

TECHNICAL DATA

CONSTRUCTION:

Single hole backsplash mount - non-mixing Sensor range - 6" - 30" - Preset/Adjustable Automatic time-out -

Preset/adjustable to 0, 15, 30 or 60 sec. Shut-off delay - Preset - Adjustable 1 to to 8 sec. In-line filter with clean-out trap Slow closing, piston operated solenoid Control circuit- solid state, AC power Solenoid valve - VSI silicone elastomer piston seal 6V DC, normally closed .4W (idle), 5W (in use) Operating pressure - 5psi to 125 psi

APPROVED FOR MANUFACTURING

JSL-46-AC

APPROVED FOR MANUFACTURING

MODEL NO.:_ JOB NAME: _

TAG/ITEM:

CUSTOMER:

-SIGNATURE: Control module- wall mountable Control/power cable - armored, vandal resistantAC Mode - Power Adapter (UL/CSA)

Standard plug-in: Input AC 120V 60Hz or 220V Output DC 12V. 0.8A/Class 2 Power cable: Armored, vandal resistant

FLOW RATE

1.5 GPM Laminar Flow Control

FINISH

Chrome plated

OPTIONS

Multi-unit adapter - serves up to (8) faucets Input AC 120V, Output DC 12V, 3A Battery power

JUST MFG. COMPANY CONTINUES TO MAKE QUALITY AND FUNCTIONALITY A MARK OF THE JUST PRODUCT LINE. WE RESERVE THE RIGHT TO CHANGE PRODUCT INFORMATION WITHOUT NOTICE. DIMENSIONS MAY CHANGE AND MAY BE SUBJECT TO CHANGE WITHOUT NOTICE. NO RESPONSIBILITY IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA. JUST MFG. CO. SINKS ARE MADE IN THE U.S.A. WHEN COMPARING OTHER BRAND PRODUCTS, BE SURE TO COMPARE USA QUALITY ALONG WITH FEATURES AND DIMENSIONS.

JUST MANUFACTURING COMPANY PH: 847-678-5150 . FAX: 847-678-6817

QTY:

 IG COMPANY
 9233 KING STREET . FRANKLIN PARK . ILLINOIS . 60131-2111

 FAX: 847-678-6817
 E-MAIL: custserv@justmfg.com
 www.justmfg.com