

Electronic Faucets

5EF-2D-DS



TAG:

Architect/Engineering Specifications:

4" deck mount electronic sensor faucet with polished chrome plated brass body with integral spout, 2.2 GPM vandal resistant aerator, AC/DC control module, temperature control mixing valve with check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements

Job Name Model Specified Variations Specified Date	_Quantity			
5 7/8" [149mm]		3 5/8" 93mm	5 3/16" [131mm] 4 7/8" [124mm] 3/4" [19mm] Maximum Thickness	

Features & Benefits:

- 4" deck mount faucet w/ polished chrome plated brass body with integral spout
- 2.2 GPM vandal resistant aerator, Series 9 (B-0199-09)
- · Water resistant control module
- Plug in AC transformer or (4) AA battery (DC) power options
- · Temperature control mixing valve w/ check valves
- 18" flexible stainless steel supply hoses w/ 3/8"
 compression connections
- · Low battery LED indicator light
- Material: Polished chrome plated brass body

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- UL 1951

Warranty: One Year (Limited)

Performance Data:

- Pressure: 20 125 psi
- Temperature: 40 °F 140 °F
- Flow Rate: 2.2 GPM @ 60 psi
- Water Consumption: @ 10 sec = .37 gal
 @ 15 sec = .55 gal







c UL us



Optional Outlets (Series 4 / VR Series 9)

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)
0.35	N/A	□ B-0199-04-N035	N/A	□ B-0199-09-N035
0.5	N/A	□ B-0199-04-N05	N/A	□ B-0199-09-N05
1.0	N/A	N/A	N/A	□ B-0199-09-LF10
1.5	□ B-0199-04-WS	S N/A	□ B-0199-09-WS	□ B-0199-09-LF15
2.2	□ B-0199-04	□ B-0199-25	Standard	□ B-0199-27

equip Foodservice Accessories





• 2 Saddleback Cove • Travelers Rest, SC 29690 Ph 800-891-4808 • Fax 800-868-0084 www.tsbrass.com