



ENDOT INDUSTRIES

PIPE AND TUBING PRODUCTS

GREEN SEWER PIPE

Sewer Line Pipe (Copper Tube Size – CTS) – ASTM D2737-12

Sewer Line Pipe (OD Controlled - IPS) - ASTM D3035-06

APPLICABLE STANDARDS:

NSF	Produced with NSF Listed Resin – PE 4710
ASTM D3350	Cell Classification 445574E (UV Stabilized)
AWWA C901	Conforms as SODR 9 & 11 (IPS) SODR 9 CTS
BOCA	Conforms as SODR 9 & 11(IPS) SODR 9 CTS
ASTM D2737	Meets PE 4710 Requirements For SDR 9
ASTM D3035	Meets PE 4710 Requirements For SDR 9, 11

GREEN SEWER SERVICE TUBING (CTS) – ASTM D2737

STANDARD OUTSIDE DIMENSION RATIO (SODR) = 9 – 250 PSI

Size	Nominal O.D.	Nominal I.D.	Min. Wall	Weight Per 100'	Part Number
¾"	0.875	0.681	.097	10.3	PSP07541010009
1"	1.125	0.875	.125	17.1	PSP10041010009
1 ¼"	1.375	1.059	.153	25.5	PSP12541010009
1 ½"	1.625	1.263	.181	35.3	PSP15041010009
2"	2.125	1.653	.236	61.0	PSP20041010009

GREEN SEWER SERVICE PIPE (IPS – OD CONTROLLED) – ASTM D3035

Size	Nominal O.D.	Nominal I.D.	Min. Wall	Weight Per 100'	Part Number
------	-----------------	-----------------	--------------	--------------------	----------------

STANDARD OUTSIDE DIMENSION RATIO (DR) = 9 - 250PSI

¾"	1.050	0.816	0.117	15.2	PSP07541010016
1"	1.315	1.023	0.146	22.7	PSP10041010016
1-1/4"	1.660	1.292	0.184	36.5	PSP12541010016
1-1/2"	1.900	1.478	0.211	47.8	PSP15041010016
2"	2.375	1.847	0.264	74.1	PSP20041010016

STANDARD OUTSIDE DIMENSION RATIO (DR) = 11 - 200 PSI

¾"	1.050	0.860	0.095	13.5	PSP07541010014
1"	1.315	1.075	0.120	19.9	PSP10041010014
1-1/4"	1.660	1.358	0.151	31.4	PSP12541010014
1-1/2"	1.900	1.554	0.173	41.1	PSP15041010014
2"	2.375	1.943	0.216	65.9	PSP20041010014

WARRANTY

Certification of Purity and Lifetime Warranty - See Warranty for Details

ENDOT INDUSTRIES, INC.

www.endot.com - e-mail info@endot.com

CORPORATE HEADQUARTERS: 60 Green Pond Road, Rockaway, NJ 07866 – 800 443 6368 – FAX 973 625 4087

TENNESSEE OPERATIONS: 400 Bohannon Avenue, Greeneville, TN 37745 – 800 438 5851 – FAX 423 639 3722

OKLAHOMA OPERATIONS: Mid America Industrial Park, Pryor Creek, OK 74361 – 800 443 6368 – FAX 973 625 4087