



SPECIFICATION

Furnish and install Corrugated Copper Water Heater Connectors as manufactured by LSP Products Group/Aqua-Flo.

DESIGN FEATURES

- Brass fittings
- High quality EPDM gasket.
- Non-toxic and sanitary
- Annealed copper for more flexibility
- Tube resists work hardening allowing for more flexibility and easier installation.
- External dielectric sleeve eliminates the need for a dielectric union.
- Defect-free tubing (100% leak tested).



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

AF/S-2014 (11-02)

CORRUGATED COPPER WATER HEATER CONNECTORS

Specification Sheet

Part Number	Description	Master Carton	Length
WCP-112-PP	3/4" FIP x 3/4" FIP	25	12"
WCP-118-PP		25	18"
WCP-124-PP		25	24"
WCP-212-PP	3/4" FIP x 3/4" Sweat	25	12"
WCP-218-PP		25	18"
WCP-224-PP		25	24"
WCP-312-PP	3/4" FIP x 3/4" PEX	25	12"
WCP-318-PP		25	18"
WCP-324-PP		25	24"

COMPLIANCES/LISTINGS

- IAPMO Listed



Material Specifications:

- Copper Tubing -Uns-C12200 (ASTM B68-86)
- Nuts & End Fittings - C36000 (CDA360) Brass
- Washer - Compliant - NSF-61
- **Working Pressure:** 125 psi maximum
- **Operating Temperature:** 40°F-180°F

Product Submittal	
Job Name	
Date	
Part Number	Quantity
Architect	
Contractor	