

**STRANDED COPPER THHN WIRE** cont'd

**Stranded Copper Wire on Spool**

This copper wire is UL listed and THHN wire. It is 19 strand copper and is 600 V as well as 90C Stranded. This comes 50 ft. per spool.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>W801-50</b>	08 Gauge, 50 ft. Spool, Black	EA	1
<b>W802-50</b>	08 Gauge, 50 ft. Spool, Red	EA	1
<b>W803-50</b>	08 Gauge, 50 ft. Spool, Green	EA	1
<b>W804-50</b>	08 Gauge, 50 ft. Spool, Blue	EA	1
<b>W101-50</b>	10 Gauge, 50 ft. Spool, Black	EA	1
<b>W102-50</b>	10 Gauge, 50 ft. Spool, Red	EA	1
<b>W103-50</b>	10 Gauge, 50 ft. Spool, Green	EA	1
<b>W104-50</b>	10 Gauge, 50 ft. Spool, Blue	EA	1
<b>W105-50</b>	10 Gauge, 50 ft. Spool, White	EA	1
<b>W121-50</b>	12 Gauge, 50 ft. Spool, Black	EA	1
<b>W122-50</b>	12 Gauge, 50 ft. Spool, Red	EA	1
<b>W123-50</b>	12 Gauge, 50 ft. Spool, Green	EA	1
<b>W124-50</b>	12 Gauge, 50 ft. Spool, Blue	EA	1
<b>W125-50</b>	12 Gauge, 50 ft. Spool, White	EA	1
<b>W141-50</b>	14 Gauge, 50 ft. Spool, Black	EA	1
<b>W142-50</b>	14 Gauge, 50 ft. Spool, Red	EA	1
<b>W143-50</b>	14 Gauge, 50 ft. Spool, Green	EA	1
<b>W144-50</b>	14 Gauge, 50 ft. Spool, Blue	EA	1
<b>W145-50</b>	14 Gauge, 50 ft. Spool, White	EA	1

**High Temperature Wire, 400°F (204°C), 600 V.**

7 strand tin coated copper wire with silicone rubber insulation protected by a braided fiberglass jacket. Use on the front of all gas furnaces with spark ignition because of flame roll out on start up. Also on all power feeds to electric strip and duct heaters. Also used on all heat producing food preparation equipment.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>WHT20</b>	14 gauge, 10 ft. black, 10 ft. white	EA	1
<b>WHTB14-50</b>	14 gauge, black, 50 ft.	EA	1
<b>WHTR14-50</b>	14 gauge, red, 50 ft.	EA	1
<b>WHTW14-50</b>	14 gauge, white, 50 ft.	EA	1
<b>WHTB12-20</b>	12 gauge, black, 20 ft.	EA	1
<b>WHTB12-50</b>	12 gauge, black, 50 ft.	EA	1
<b>WHTB10-20</b>	10 gauge, black, 20 ft.	EA	1
<b>WHTB10-50</b>	10 gauge, black, 50 ft.	EA	1

**WIRE CONNECTORS**

**Wire Connectors—Screw On, U.L. Listed, C.S.A Approved**

Color coded connectors make quick, secure connections for positive continuity. High dielectric thermoplastic shell resists chemical action from hydrocarbons, dilute acid or alkaline solutions. Deep skirt design prevents exposure of bare wire.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>623-001</b>	Gray Screw-On – Size 71B, #22 to #16 AWG, 300V Max., pack of 100	PK	1
<b>623-002</b>	Blue Screw-On – Size 72B, #22 to #16 AWG, 300V Max., pack of 100	PK	1
<b>623-003</b>	Orange Screw-On – Size 73B, #22 to #14 AWG, 600V Max., pack of 100	PK	1
<b>623-004</b>	Yellow Screw-On – Size 74B, #18 to #10 AWG, 600V Max., pack of 100	PK	1
<b>623-005</b>	Red Screw-On – Size 76B, #18 to #10 AWG, 600V Max., pack of 100	PK	1
<b>623-MIX</b>	Wire connector assortment, Pack of 570	PK	1

U.L. Listed, CSA Approved.

**Wire Connectors—Winged, U.L. Listed, C.S.A Approved**

Wings give surer grip; offset center design provides great twisting leverage. Expandable square-wire spring instantly adjusts to shape and size to create a strong, vibration-resistant connection. Same tough shell as screw-on type.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>623-000</b>	Lg. Gray Winged – Size 78B, #14 to #8 AWG, 600V Max., pack of 50	PK	1
<b>623-006</b>	Yellow Winged – Size 84, #22 to #10 AWG, 600V Max., pack of 100	PK	1
<b>623-007</b>	Red Winged – Size 86, #18 to #10 AWG, 600V Max., pack of 100	PK	1
<b>623-008</b>	Blue Winged – Size 89, #10 to #6, 600V Max., pack of 50	PK	1

U.L. Listed, C.S.A. Approved.