



**CERTIFIED FOR:** \_\_\_\_\_  
**JOB NAME:** \_\_\_\_\_  
**LOCATION:** \_\_\_\_\_  
**CUSTOMER:** \_\_\_\_\_  
**CUSTOMER P.O.:** \_\_\_\_\_

**Submittal Information: MPH-24FP:24/9 Pedestal Hydrant**



**Composition:**

- Black painted cast aluminum Weather-Guard Dome Handle
- Grade 304 stainless steel shroud w/ welded stainless steel flange
- 125 psi, 1" Bronze Globe Angle Valve / Male Hose Fitting / Quick Disconnect w/ Built-in Vacuum Breaker
- Stainless steel reservoir

**Insulation:**

- R-8 rated / Thermo-Cell insulation

**Mounting Hardware:**

- Black painted under-deck support flange w/ hardware

**Options:**

Suffix "D" – Deck Cap

Suffix: xx/yy – Extended shroud for above or below roofline – 6" increments

**Practical Application**

Where there is concern for potential damage to the hydrant assembly due to severe cold weather, the MPH-24FP:24/9 Pedestal Hydrant with its Weather-Guard Dome provides a freeze proof hose station at required locations. The Stainless Steel Shroud and Base allow the contractor to make a positive, weather tight flashing to the hydrant in rooftop applications. The hydrant meets ASSE 1057 Sanitary Yard Hydrant Standard.

**Features**

- The Weather-Guard Domed Handle enables the user to operate the valve assembly while preventing moisture from entering the assembly when the valve is in the OFF position.
- The hydrant utilizes the best bronze valves within a fully insulated stainless steel shroud.
- The quick disconnect/vacuum breaker provided allows a hose to be readily removed when not in use so as to insure proper evacuation of the reservoir during freezing conditions.
- The Under-deck Flange prevents the Hydrant from becoming dislodged from the roof membrane during operation.

**Warranty:**

Limited Lifetime Warranty--When installed in accordance with MAPA installation and maintenance specifications and using only MAPA materials, MAPA warrants its support bases and assemblies to be free from defect and will repair or replace product at MAPA's discretion. Rusting that is not detrimental to the integrity of the support is not warranted. Damage caused by incorrect installation, improper usage or improper maintenance is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

**Limits of Liability:**

ISIMET/MAPA liability shall be limited to costs of repair or replacement parts. Supports are not intended for usage other than those expressly described in product catalog. ISIMET/MAPA does not perform engineering design and shall not be liable for damage or injury caused by the improper use or installation of the product.

**CERTIFICATION DATA**

QUANTITY	STYLE Roof/Yard	Deck Cap	Extended Length	Dimensions (If other than Standard 24" above roofline)	Notes
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		

<b>DRAWN</b>	<b>CHECKED</b>	<b>DATE</b>	<b>DWG.NO.</b>
--------------	----------------	-------------	----------------

Effective Date January 2020

OP2009-MPH24FP  
Doc. #: M-13503