

## Zinc Die Cast

Catalog Number	K.O. Size	Metal Clad Cable Range		Unit Qty.	Std. Pkg. Qty.
		Min.	Max.		
565-DC2	1/2"	.440"	.525"	100	1000
566-DC2	1/2"	.440"	.525"	100	1000

## Two Screw, Strap Type Connector




565-DC2



566-DC2

For connecting 14/2 to 10/3 armored or metal clad cable to box or enclosure. The 566-DC2 is also approved for use with MCI-A Cable 14/4 (.43" Ø min) to 10/3 (.53" Ø max). The 565-DC2 is approved for MCI-A Cable 14/2 (.43" Ø min) to 10/3 (.53" Ø max).

 File No. E20534

## Zinc Die Cast

Catalog Number	Trade Size	K.O. Size	Cable Range		Unit. Qty.	Std. Pkg. Qty.
			Min.	Max.		
570-DC2	3/8"	1/2"	.440"	.610"	50	500
570-DCR2	3/8"	1/2"	.440"	.610"	50	500

## Zinc Die Cast / Insulated Throat - 105°C

Catalog Number	Trade Size	K.O. Size	Cable Range		Unit. Qty.	Std. Pkg. Qty.
			Min.	Max.		
570-DCI2	3/8"	1/2"	.440"	.610"	50	500

## Low Profile "U" Shaped Strap Connectors



570-DC2




570-DCI2



570-DCR2

Used to connect 14/2 to 10/3 armored and metal clad cable to box or enclosure. The 570-DC2 is approved for use with MCI-A Cable 14/2 (.38" Ø min) to 10/3 (.53" Ø max). The 570-DCI2 and the 570-DCR2 are approved for use with MCI-A Cable 14/4 (.43" Ø min) to 10/3 (.53" Ø max).

 File No. E20534