

ADJUSTABLE CLEANOUT

851 SERIES

SPECIFICATION

Sioux Chief 851 Series adjustable cleanout shall be used where necessary in drainage systems. Cleanout shall have a cast iron push-joint connection. Cleanout cover shall meet applicable load requirements for intended use. Cleanout shall include a slotted, polypropylene cleanout plug, with threaded brass insert to accept cover screw.

MATERIALS

- Adapter body: cast iron
- Push-joint gasket: neoprene
- Ring/cover: nickel-bronze, tenz alloy or cast iron
- Set screws: square head, 1/4-20
- Cover screw: stainless steel, Phillips head, 1/4-20
- Cleanout plug: slotted polypropylene with threaded brass insert

COVER LOAD RATING

- Nickel-bronze: 1,000 lbs. (medium duty)
- Tenz alloy: 750 lbs. (light duty)
- Cast iron: 7,500 lbs. (heavy duty)


DIMENSIONS

	Nickel-Bronze/ Tenz alloy	Cast Iron
A: ring/cover diameter		
4" cleanout	6"	6"
6" cleanout	8 3/8"	8 3/8"
B: height		
4" cleanout	3 1/4" - 4 1/2"	4 3/4" - 5 3/4"
6" cleanout	3 7/8" - 5"	4 1/2" - 6"
C: plug		
4" cleanout	4" MIP	4" MIP
6" cleanout	5" MIP	5" MIP

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



851-64N



Create Item Number

851-ABC

e.g. 851-63iNV: 3" connection cast iron push-joint cleanout with nickel-bronze laminated cast iron cover and vandal-proof screw

CONNECTION TYPE A

- 64 = ABS adapter
- 66 = PVC adapter

RING & COVER B

- N = nickel-bronze
- T = tenz alloy
- i = cast iron

OPTIONS (FACTORY INSTALLED) C

- V = vandal-resistant cover screws
- S = stamped cover, specify letters¹
- C = carpet marker
- P = push-joint gasket for Sch. 40 ABS/PVC pipe²

¹NOT available for cast iron ring & cover

²Only for 4" cleanouts