


FIG. 3205R

Reducing Tee



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

FIGURE 3205R - REDUCING TEE

Nominal Size	Max. Working Pressure▲	Dimensions			Approx. Wt. Each
		A	B	C	
1 x 2 x 3					
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1 x ½ x 1 25 x 15 x 25	500 3450	1.50 38.10	1.36 34.54	1.50 38.10	0.64 0.29
1 x ¾ x 1 25 x 20 x 25	500 3450	1.50 38.10	1.45 36.83	1.50 38.10	0.73 0.33
1 x 1 x ½ 25 x 25 x 15	500 3450	1.26 32.00	1.26 32.00	1.36 34.54	0.71 0.32
1 x 1 x ¾ 25 x 25 x 20	500 3450	1.37 34.80	1.37 34.80	1.45 36.83	0.76 0.34
1 x 1 x 1¼* 25 x 25 x 32	500 3450	1.67 42.41	1.67 42.41	1.58 40.13	0.98 0.44
1 x 1 x 1½* 25 x 25 x 40	500 3450	1.80 45.72	1.80 45.72	1.65 41.91	1.16 0.53
1¼ x 1 x ½* 32 x 25 x 15	500 3450	1.34 34.04	1.26 32.00	1.53 38.86	0.82 0.37
1¼ x 1 x ¾ 32 x 25 x 20	500 3450	1.45 36.83	1.37 34.80	1.62 41.15	0.90 0.41
1¼ x 1 x 1 32 x 25 x 25	500 3450	1.58 40.13	1.50 38.10	1.67 42.42	1.00 0.45
1¼ x 1 x 1¼ 32 x 25 x 32	500 3450	1.75 44.45	1.67 42.42	1.75 44.45	1.08 0.49
1¼ x 1 x 1½ 32 x 25 x 40	500 3450	1.88 47.75	1.80 45.72	1.82 46.22	1.42 0.64
1¼ x 1¼ x ½ 32 x 32 x 15	500 3450	1.34 34.04	1.34 34.04	1.53 38.86	0.86 0.39

▲ Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit anvilintl.com or contact your local Anvil Representative.

* Part supplied as "Bull Head Tee".

MATERIAL SPECIFICATIONS

Dimensions: ASME B16.3

Material: ASTM A536 Grade 65-45-12

Finish: Black

Threads: NPT per ASME B1.20.1

Agency Approvals: All ductile iron threaded fittings are UL/ULC Listed and FM Approved.

NOTICE: Ductile iron fittings have higher tensile strength than that of steel pipe. Therefore, over tightening can cause damage to pipe threads which may cause leakage. Ductile iron fittings should be tightened approximately three turns beyond hand tight, but no more than four turns.

FIGURE 3205R - REDUCING TEE

Nominal Size	Max. Working Pressure▲	Dimensions			Approx. Wt. Each
		A	B	C	
1 x 2 x 3					
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1¼ x 1¼ x ¾ 32 x 32 x 20	500 3450	1.45 36.83	1.45 36.83	1.62 41.15	0.92 0.42
1¼ x 1¼ x 1 32 x 32 x 25	500 3450	1.58 40.13	1.58 40.13	1.67 42.42	0.95 0.43
1¼ x 1¼ x 1½* 32 x 32 x 40	500 3450	1.88 47.75	1.88 47.75	1.82 46.22	1.45 0.66

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	

FIG. 3205R

Reducing Tee




FIGURE 3205R - REDUCING TEE					
Nominal Size	Max. Working Pressure▲	Dimensions			Approx. Wt. Each
1 x 2 x 3		A	B	C	
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1¼ x 1¼ x 2*	500 3450	2.10 53.34	2.10 53.34	1.90 48.26	1.75 0.79
1½ x 1 x ½	500 3450	1.41 35.81	1.34 34.04	1.66 42.16	0.95 0.43
1½ x 1 x ¾	500 3450	1.52 38.61	1.37 34.80	1.75 44.45	1.14 0.52
1½ x 1 x 1	500 3450	1.65 41.91	1.50 38.10	1.80 45.72	1.17 0.53
1½ x 1 x 1¼	500 3450	1.82 46.23	1.67 42.42	1.88 47.75	1.34 0.61
1½ x 1 x 1½	500 3450	1.94 49.28	1.80 45.72	1.94 49.28	1.45 0.66
1½ x 1¼ x ½	500 3450	1.41 35.81	1.34 34.04	1.66 42.16	1.05 0.48
1½ x 1¼ x ¾	500 3450	1.52 38.61	1.45 36.83	1.75 44.45	1.15 0.5
1½ x 1¼ x 1	500 3450	1.65 41.91	1.58 40.13	1.80 45.72	1.25 0.57
1½ x 1¼ x 2*	500 3450	2.16 54.86	2.10 53.34	2.02 51.30	1.90 0.86
1½ x 1½ x ½	500 3450	1.41 35.81	1.41 35.81	1.16 29.46	1.15 0.52
1½ x 1½ x ¾	500 3450	1.52 38.61	1.52 38.61	1.75 44.45	1.24 0.56
1½ x 1½ x 1	500 3450	1.65 41.91	1.65 41.91	1.80 45.72	1.30 0.59
1½ x 1½ x 1¼	500 3450	1.82 46.23	1.82 46.23	1.88 47.75	1.48 0.67

FIGURE 3205R - REDUCING TEE					
Nominal Size	Max. Working Pressure▲	Dimensions			Approx. Wt. Each
1 x 2 x 3		A	B	C	
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1½ x 1½ x 2*	500 3450	2.16 54.86	2.16 54.86	2.02 51.30	1.98 0.90
2 x 1 x 2	500 3450	2.25 57.15	2.02 51.31	2.25 57.15	2.15 0.98
2 x 1¼ x 2	500 3450	2.25 57.15	2.10 53.34	2.25 57.15	2.30 1.04
2 x 1½ x ½	500 3450	1.49 37.85	1.41 35.81	1.88 47.75	1.50 0.68
2 x 1½ x ¾	500 3450	1.60 40.64	1.52 38.61	1.97 50.04	1.62 0.73
2 x 1½ x 1	500 3450	1.73 43.94	1.65 41.91	2.02 51.31	1.64 0.74
2 x 1½ x 1¼	500 3450	1.90 48.26	1.82 46.23	2.10 53.34	1.80 0.82
2 x 1½ x 1½	500 3450	2.02 51.31	1.94 49.28	2.16 54.86	2.00 0.91
2 x 1½ x 2	500 3450	2.25 57.15	2.16 54.86	2.25 57.15	2.35 1.07
2 x 2 x ½	500 3450	1.49 37.85	1.49 37.85	1.88 47.75	1.60 0.73
2 x 2 x ¾	500 3450	1.60 40.64	1.60 40.64	1.97 50.04	1.68 0.76
2 x 2 x 1	500 3450	1.73 43.94	1.73 43.94	2.02 51.31	1.85 0.84
2 x 2 x 1¼	500 3450	1.90 48.26	1.90 48.26	2.10 53.34	2.04 0.93
2 x 2 x 1½	500 3450	2.02 51.31	2.02 51.31	2.16 54.86	2.18 0.99

▲ Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit anvilintl.com or contact your local Anvil Representative.

* Part supplied as "Bull Head Tee".