



STARTEK

Item Number 4507917

Electronic, compact leak detector for all halogenated refrigerants

- Detects all halogen-based refrigerants
- Device complies with SAE J1627, EN 14624 standard
- Easy handling thanks to one-button operation
- Sensitivity levels selectable with double click
- Automatic recalibration
- Leakage is indicated by optical and acoustic signals
- Auto-Shutoff
- In a practical holster with belt clip
- Replacement sensor in battery compartment
- In a sturdy plastic case

Technical Data

Color	green (RAL 6026) yellow (RAL 1023)
Standards	SAE J1627 EN 14624 EN 61326-1:2013 EN 55011 :2018-05 EN 61000-4-2 :2009-12 EN 61000-4-3 :2011-04 EN 50581:2012
RoHS Conformity	Yes
Refrigerant(s)	R12 R134a R22 more
Operating Temperature Range	32 - 122 °F
Battery	2 x AA
Operating Hours	40 h
Sensitivity	< 0.1 oz/yr

Acknowledged globally



Refrigerant Type	Refrigerants CFC HCFC HCF HFO
Measurement Technology	Negative Corona
Tube Length	12 "
Scope of Supply	Batteries Case Instruction manual
Packaging	Sturdy plastic case
Warm-up Time	2 s

Spare Parts

4507577	ES-02/2	Replacement sensors for STARTEK leak detector, 2 pieces
---------	---------	---