

Leak Detection

STARTEK

Electronic Leak Detector for all Halogenated Refrigerants

- Extremely compact design concept similar to a cell phone
- Ergonomical design focused on performance and simplicity of operation
- Microprocessor controlled unit and state of the art microelectronics
- Detects all halogenated refrigerants incl. R410A
- Certified to SAE J1627 standard
- Simple one-button operation
- Two sensitivity levels using a double-click computer mouse action
- One touch reset-mode
- High performance true mechanical pump to provide positive airflow through the sensing tip
- Leak indication using both variable frequency audible and visual alarm
- Automatic shut-off after extended period of non-use to preserve battery life
- Battery life indicator
- Prevents incorrect readings by providing visual and audible warning followed by an automating shut-off when battery reaches a critical level
- State of the art sensor technology for higher reliability and longer life time
- Includes a practical belt clip holster that also protects the unit in your tool box
- Specially designed 12" flexible probe for easy reach
- Additional replacement sensor included inside the battery compartment
- Packed up in a sturdy plastic case

Technical Data:

Dimensions:	6 x 1.4 x 2.1 inch
Weight:	6.7 oz
Batteries:	2 x AA batteries
Battery lifetime:	40 hours
Sensitivity:	less than 0.1 oz/year
Sensor lifetime:	approx. 30 hours
Operating temperature:	32° to 125° F
Warm up time:	less than 2 seconds
Response time:	instantaneous
Reset time:	instantaneous
Probe length:	12 inches
Warranty:	2 years

Part No. 4507917

Designation	Description	Part No.
ES-02	Replacement sensor (Pack of 2)	4507577
STARTEK-CASE	Carrying case for STARTEK	4664333



STARTEK-CASE



STARTEK

