Fire Department Connections



Models 6350-6355





Ordering Options

- ☐ Standard unit
- ☐ Storz adapter & cap (no plate)

Optional Finish

- □ PB Polished Brass
- □ PC Polished Chrome

Optional Plate Lettering

- ☐ S "STANDPIPE"
- ☐ C "STANDPIPE AUTO SPKR"
- ☐ Custom

Croker Division Fire-End & Croker Corporation 7 Westchester Plaza Elmsford, NY 10523

1-800-759-FIRE info@croker.com www.croker.com

Application

Serves as an auxiliary inlet fire department connection to supplement fire protection water supply.

Standard Features

Storz universal threadless connections reduce connect time compared to traditional threaded ends and allow large volume water transfer with large diameter hose. 30° units are designed for wall mount installation. The 30° elbow reduces hose kinking. The lugged Storz head and cap make installation easy with standard wrenches in the market. The nitrile gasket seals the Storz head and cap. This seal prevents moisture and foreign matter from entering the connection. The stainless steel locking lever keeps the cap engaged and is a means for the installer to know when the seal is complete. Each connection comes standard with a stainless steel internal screen to prevent debris from entering the system, and a weep hole on the cap to prevent pressure from building up.

- 250 psi rated 30° forged T6160 aluminum adapter with Storz inlet, female NPT rigid rocker lug outlet, nitrile gasket, stainless steel locking lever, stainless steel internal screen, "Silvadillo" silver powder coat finish, and cap with chain and weep hole.
- Red aluminum "AUTO SPKR" identification plate.

Optional Features

- Polished brass finished adapter, cap, and plate.
- Polished chrome finished adapter, cap, and plate.
- Alternative lettering on plate. Custom lettering is available.

Available Models

		Weight
Model	Size	(lbs.)
□ 6350	4" Fe NPT x 4" Storz	8
□ 6352	4" Fe NPT x 5" Storz	13
□ 6353	6" Fe NPT x 4" Storz	15
□ 6354	6" Fe NPT x 5" Storz	19
□ 6355	6" Fe NPT x 6" Storz	21

★ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov