

SeeSnake® Reels and Cameras

NEW
COMING IN 2019



SeeSnake Standard Reel



RIDGID® SEESNAKE STANDARD WITH TRUSENSE™

The SeeSnake Standard camera reel offers unmatched reliability and performance in a ruggedized package. It is newly available with TruSense™ technology.



Best Use: The Standard has the stiffest push cable and is available in lengths up to 325' (99 m) – making it perfect for long runs, particularly in larger pipes with fewer turns.

FEATURES

- Rugged, high-intensity LEDs for exceptional viewing and long life.
- Self-leveling camera head option to keep the image upright.
- Powerful FleXmitter® sonde has long range and preserves the camera's ability to make turns.
- High dynamic range (HDR) image sensor offers bright, clear in-pipe imaging in difficult lighting conditions.
- TiltSense data sensor displays the camera's degree pitch in pipe on a connected SeeSnake CSx series monitor.
- Included pipe guides center the camera for better in-pipe imaging.

SPECIFICATIONS

	SeeSnake Standard	
Rated Pipe Capacity	2" to 12" (51 mm to 305 mm)	2" to 12" (51 mm to 305 mm)
CABLE		
Max Cable Length	325' (99 m) / 200' (61 m)	325' (99 m) / 200' (61 m)
Minimum Bend Radius	4.5" (114 mm)	4.5" (114 mm)
CAMERA		
Style	Fixed TruSense	Self-Leveling TruSense
Diameter	1.4" (35 mm)	1.4" (35 mm)
Length	1.2" (31 mm)	1" (26 mm)
SONDE		
Frequency	512 Hz	512 Hz
Type	FleXmitter	FleXmitter
DISTANCE MEASUREMENT		
Type	TruSense Counter	TruSense Counter
Data Communication	Two-Way	Two-Way

Catalog No.	Description	Weight	
		lb	kg
63583	325' Standard 35 mm SL TruSense	54	24
63588	325' Standard 35 mm TruSense	54	24
63603	200' Standard 35 mm SL TruSense	42	19
63613	200' Standard 35 mm TruSense	42	19

Accessories

Catalog No.	Description
64497	75 mm Star Guide, 35 mm Camera, Pkg of 20
97852	85 mm Pipe Guide, 35 mm Camera, Pkg of 10
64502	150 mm Pipe Guide, 35 mm Camera, Pkg of 10
93387	Guide Hoop, 35mm Camera, Pkg of 4
97832	75 mm Roller Dolly, up to 6" Pipe
17563	Spanner Wrench, 35 mm



SeeSnake Standard Camera with Roller Dolly

Replacement Parts

Catalog No.	Description
63833	35 mm Self-Leveling Camera Head - TruSense
63838	35 mm Fixed Camera Head - TruSense
35103	325' SeeSnake Standard Push Cable Assembly
35108	200' SeeSnake Standard Push Cable Assembly
64627	Interconnect Cable, 33' SeeSnake Standard
48543	35 mm Self-Leveling Camera Head - NTSC
14078	35 mm Fixed Camera Head - NTSC