




Schedule 80 PVC Technical Schedule 80 Tank Adapters

Tank Adapters, PVC New Style Standard with Neoprene Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°
F (23°C)

Dimensions Also Applicable to
8171E-XXX & 8171V-XXX




Part Number	Size	L	L1	M	M1	N	R	Min Hole Size	Approx. Wt. (Lbs.)
8171-002	1/4	2-15/32	1-13/16	1-17/32	1-1/32	1- 1/4	1/2	1-1/16	.11
8171-003	3/8	2- 1/2	1-27/32	1-21/32	1-5/32	1- 3/16	1/2	1-3/16	.12
8171-005	1/2	2-29/32	2- 3/16	2- 1/16	1-7/16	1-5/16	5/8	1-1/2	.21
8171-007	3/4	2-15/16	2-3/16	2- 1/4	1- 5/8	1- 3/16	5/8	1-3/4	.24
8171-010	1	3-9/32	2-9/16	2-21/32	1-31/32	1- 1/4	5/8	2	.36
8171-012	1-1/4	3-13/32	2-5/8	3-1/8	2- 5/16	1-7/32	5/8	2-3/8	.48
8171-015	1-1/2	3- 5/8	2-13/16	3- 5/8	2-11/16	1-9/32	5/8	2-3/4	.68
8171-020	2	4- 1/8	3- 1/4	4- 7/8	3- 1/4	1- 5/8	3/4	3-3/8	1.26
8171-025	2-1/2	4-27/32	3-29/32	5- 1/4	3-13/16	1-3/4	1	3-7/8	2.22
8171-030	3	5- 1/2	4- 1/2	6	4-17/32	2- 3/16	1	4-5/8	2.64
8171-040	4	4-31/32	3-15/16	7-7/16	5-7/16	1-7/32	1- 1/4	5-1/2	3.24
8171-060	6	5	4	10-3/32	8	1/32	1- 1/4	8	5.59

Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°
F (23°C)

Dimensions Also Applicable to
8171E-XXXSR & 8171V-XXXSR



Part Number	Size	L	L1	M	M1	N	R	Min Hole Size	Approx. Wt. (Lbs.)
8171-002SR	1/4	2- 1/2	1-13/16	1-17/32	1-1/32	1-9/32	1/2	1-1/16	.11
8171-003SR	3/8	2-17/32	1-27/32	1-21/32	1-5/32	1- 3/16	1/2	1-3/16	.12
8171-005SR	1/2	2-15/16	2-3/16	2- 1/16	1-15/32	1-5/16	5/8	1-1/2	.22
8171-007SR	3/4	2-15/16	2-7/32	2- 1/4	1- 5/8	1- 1/4	5/8	1-3/4	.25
8171-010SR	1	3- 5/16	2-9/16	2-21/32	1-31/32	1-9/32	5/8	2	.38
8171-012SR	1-1/4	3-7/16	2-21/32	3-1/8	2- 5/16	1-1/4	5/8	2-3/8	.51
8171-015SR	1-1/2	3- 5/8	2-13/16	3- 5/8	2-11/16	1-9/32	5/8	2-3/4	.69
8171-020SR	2	4- 1/8	3- 1/4	4- 7/8	3- 1/4	1- 5/8	3/4	3-3/8	1.31
8171-025SR	2-1/2	4- 7/8	3-29/32	5- 1/4	3-13/16	1-13/16	1	3-7/8	2.26
8171-030SR	3	5- 1/2	4- 1/2	5-31/32	4-1/2	2- 3/16	1	4-5/8	2.70
8171-040SR	4	5	4	7-7/16	5-7/16	1- 1/4	1- 1/4	5-1/2	3.36
8171-060SR	6	5	4-3/32	10-3/32	8	1/32	1- 1/4	8	7.13