Electronic Accessories

060704A – Hardwire Transformer


RP32508 – Hardwire Transformer

SPECIFICATIONS

General: Supplies power for up to ten Delta Commercial 590 HDF or 860T Series, up to five 3000T, 1500T, 590TP, 590TP, 591TP, 1600T, 81THW, DEMD, 600T, 620TP or 630TP electronic units already converted to hardwire

Input Voltage: 120 VAC @ 60 Hz Output Voltage (unloaded): 24 VAC ± 3% @ 20 VA Maximum Output Current: 800 mA Physical Connections: Universal Mounting Clip Terminals: Screw Type

Safety Approval: UL Listed Class 2 CSA Certified



060771A - Hardwire Transformer

SPECIFICATIONS


General: Supplies power for up to ten 3000T, 1500T, 590T, 590TP, 591T, 591TP, 1600T, 81THW, DEMD, 600T, 620TP, 630TP

Input Voltage: 120 V

Output Voltage (unloaded): 24 VAC

Maximum Output Current: 1.67 A

Physical Connections: Universal Mounting Clip Terminals: Screw Type Safety Approval: UL Listed Class 2 CSA Certified



060683A - Hardwire Converter

SPECIFICATIONS

General: Converts Delta Commercial 590, 591 and 592 Series battery electronic faucets to hardwire Input Voltage: 24 VAC @ 60 Hz Output Voltage: 6.4 VDC ± 5% Maximum Output Current: 150 mA Operating Temperature Range: -55°C to 85°C Physical Connections: #22 AWG Stripped Primary Connection / 9 VDC Snap Secondary Connection Wire Size: #22 AWG Wire Length: 18.0" Wire Ends: Strip length of wires should be 0.375" typical



RP32856 – Plug-In Transformer

TEC

COMMERCIAL

SPECIFICATIONS

General: Supplies power for up to ten Delta Commercial 590 HDF or 860T Series, up to five 3000T, 1500T, 590T, 590TP, 591T, 591TP, 1600T, 81THW, DEMD, 600T, 620TP or 630TP electronic units already converted to hardwire

Input Voltage: 100-240 V @ 50-60 Hz


Output Voltage (unloaded): $12 \text{ VAC} \pm 5\% @ 24 \text{ VA}$

Maximum Output Current: 2 A

Operating Temperature Range: 0°C to 45°C **Physical Connections:** Plug-In Connection

Terminals: Screw Type

Safety Approval: UL Listed Class 2 Efficiency Level VI FCC



Refer to www.specselect.com for individual models.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.