




Schedule 40 Fittings Technical

Schedule 40 Fittings Dimensions & Information

45° Street Ell

Spigot x Socket

(Continued)




Part Number	Size	H	H1	J	J1	M1	Approx. Wt. (Lbs.)
427-015	1-1/2	2- 1/32	1-3/4	11/16	7/16	2-1/4	.19
427-020	2	2	2	5/8	5/8	2-23/32	.30
427-025	2-1/2	2- 5/8	2- 5/8	3/4	7/8	3-11/32	.59
427-030	3	2-31/32	3- 1/32	1	1- 7/32	4- 5/32	1.18
427-040	4	3-29/32	3-5/16	1-1/32	1-1/16	5-1/4	2.14
427-050	5	6- 1/8	4- 3/8	2- 7/8	1- 3/8	6- 1/16	3.64
427-060	6	5- 1/4	6- 1/4	1- 3/4	3	7- 5/8	5.72
427-080	8	6- 5/8	5-31/32	2-19/32	1- 3/4	9- 3/4	10.59
427-140F*	14	11-7/16	11-7/16	4-7/16	4-7/16	14-7/8	22.00
427-160F*	16	18-1/8	13-1/8	9-1/8	5-1/8	17	44.00
427-180F*	18	20-3/8	14-7/8	10-3/8	5-7/8	19-1/8	66.00
427-200F*	20	22-9/16	16-9/16	11-9/16	6-9/16	21-3/16	84.00
427-240F*	24	26-15/16	19-15/16	13-15/16	7-15/16	25-3/8	154.23

* Fabricated

15° Ell

Socket x Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
418-005F*	1/2	1- 5/16	5/16	1- 1/16	.04
418-007F*	3/4	1- 5/16	5/16	1- 1/4	.07
418-010F*	1	1- 5/8	3/8	1- 9/16	.09
418-012F*	1-1/4	2	1/2	1-15/16	.18
418-015F*	1-1/2	2	1/2	2- 3/16	.22
418-020F*	2	2- 5/16	9/16	2-11/16	.29
418-025F*	2-1/2	2- 3/4	3/4	3- 1/4	.57
418-030F*	3	3	3/4	3-15/16	.77
418-040F*	4	3-1/16	13/16	5	1.36
418-045F*	4-1/2	3- 3/8	7/8	5- 7/16	1.35
418-050F*	5	3- 7/8	7/8	6- 1/16	1.88
418-060F*	6	4- 3/8	1- 1/8	7- 3/16	2.66
418-080F*	8	5- 1/2	1- 1/4	9- 1/4	5.95
418-100F*	10	6-7/8	1-5/8	11- 1/2	9.41
418-120F*	12	8	1-3/4	13- 9/16	14.09