

## Dixon® Type B Couplers coupler x male NPT



356T6 aluminum



aluminum hard coat



brass



unplated malleable iron



316 stainless steel

**Features:**

- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 167 - 170.
- ½" Dixon® coupler has only one cam arm.
- Pull rings are not supplied on ½" - 1" Dixon® couplings.

Size	356T6 Aluminum Part #	Aluminum Hard Coat Part #	Brass Part #
½"	<b>50-B-AL</b>	---	<b>50-B-BR</b>
¾"	<b>75-B-AL</b>	---	<b>75-B-BR</b>
1"	<b>100-B-AL</b>	---	<b>100-B-BR</b>
1¼"	<b>125-B-AL</b>	---	---
1½"	<b>150-B-AL</b>	<b>150-B-ALH</b>	<b>150-B-BR</b>
2"	<b>200-B-AL</b>	<b>200-B-ALH</b>	<b>200-B-BR</b>
2½"	<b>250-B-AL</b>	---	---
3"	<b>300-B-AL</b>	<b>300-B-ALH</b>	<b>300-B-BR</b>
4"	<b>400-B-AL</b>	<b>400-B-ALH</b>	<b>400-B-BR</b>
5"	<b>500-B-AL</b>	---	---
6"	<b>600-B-AL</b>	<b>600-B-ALH</b>	---
8"	<b>800-B-AL</b> <sup>1,2</sup>	---	---

<sup>1</sup> Dixon® and Boss-Lock™ cam & groove couplings *do not interchange in the 8" size*. The 8" Dixon® design has 4 cam arms.

<sup>2</sup> Parts are produced as a welded fabrication.

Size	Unplated Malleable Iron Part #	316 Stainless Steel Part #
½"	---	<b>50-B-SS</b>
¾"	---	<b>75-B-SS</b>
1"	---	<b>100-B-SS</b>
1½"	<b>150-B-MI</b> <sup>1</sup>	<b>150-B-SS</b>
2"	<b>200-B-MI</b>	<b>200-B-SS</b>
2½"	---	<b>250-B-SS</b>
3"	<b>300-B-MI</b> <sup>1</sup>	<b>300-B-SS</b>
4"	<b>400-B-MI</b>	<b>400-B-SS</b>
6"	---	<b>600-B-SS</b>

<sup>1</sup> ductile iron