

PRO-STRIPE INVERTED AEROSOL MARKING PAINT #MP-SPEC

PRODUCT DESCRIPTION

PRODUCT

PRO-STRIPE Inverted Aerosol Marking Paint

TYPE

Water Based VT Modified High Solids Alkyd Resin Marking Paint

RECOMMENDED USES

Use in marking construction, excavation sites, underground utilities, landscaping, sports turf marking, graphics, logos and general surveying. Colors meet American Public Works Association (APWA) Uniform Color Code for marking underground facilities. All **PRO-STRIPE** inverted markers are lead free and the water based formula allows for use on lawns without damaging the grass. Durable enough for traffic marking, marking; gas lines, electric lines, utilities, and water lines.

PHYSICAL PROPERTIES

COLORS

Black	Hot Orange
Blue	Pink
Cloud White	Red
Green	Yellow

TEMPERATURE RANGE USE

35°F (2°C) to 90°F (32°C)

COVERAGE

Up to 500 lineal feet. Coverage is dependent on surface porosity.

DRYING TIME*

Handling: 15 minutes @ 72°F (22°C)
30 minutes @ 35°F (2°C)

SHEEN / FINISH

Flat to semi-gloss finish
(dependent on surface)

ENVIRONMENTAL STATEMENT

Meets APWA color standards and is V.O.C. Compliant

#MP-SPEC

© 2019 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

*Note: Drying time can be affected by humidity and temperature and may vary greatly ±.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.

APPLICATION PRECAUTIONS

WARNING:
PRESSURIZED CONTAINER;
PROTECT FROM SUNLIGHT AND
DO NOT EXPOSE TO
TEMPERATURES EXCEEDING
122°F (50°C). DO NOT PIERCE OR
BURN, EVEN AFTER USE.
EXTREMELY FLAMMABLE
LIQUID AND VAPOR.
KEEP AWAY FROM HEAT,
SPARKS AND FLAME.

HARMFUL OR FATAL IF SWALLOWED.
USE WITH ADEQUATE VENTILATION.
AVOID PROLONGED BREATHING OF
VAPORS. AVOID CONTACT WITH
EYES OR SKIN. KEEP OUT OF REACH
OF CHILDREN. SEE SAFETY DATA
SHEET (SDS) FOR COMPLETE
PRECAUTIONS FOR SAFE HANDLING
AND USE.

Do not warehouse in temperatures
below 32°F (0°C). Keep from freezing.

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Aerosol Can	
#MP-BLACK	17 oz. (503 ml)
#MP-BLUE	17 oz. (503 ml)
#MP-CLOUD WHITE	17 oz. (503 ml)
#MP-GREEN	17 oz. (503 ml)
#MP-HOT ORANGE	17 oz. (503 ml)
#MP-PINK	17 oz. (503 ml)
#MP-RED	17 oz. (503 ml)
#MP-YELLOW	17 oz. (503 ml)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>
#MP-BLACK	19 lbs. (8.6 kg)
#MP-BLUE	19 lbs. (8.6 kg)
#MP-CLOUD WHITE	19 lbs. (8.6 kg)
#MP-GREEN	19 lbs. (8.6 kg)
#MP-HOT ORANGE	19 lbs. (8.6 kg)
#MP-PINK	19 lbs. (8.6 kg)
#MP-RED	19 lbs. (8.6 kg)
#MP-YELLOW	19 lbs. (8.6 kg)

Items per case = 12 cans

SHIPPING CLASSIFICATION:

Consumer Commodity ORM.D, UN1950

APPLICATION DIRECTIONS:

1. For best results use when can temperature is between 40°F (5°C) to 90°F (32°C). Can be sprayed by hand or with a "Pro-Striper" Marking Gun (#704) or the "Pro-Striper" Marking Wand (#705).
2. Shake can at least one minute after rattle is heard and occasionally during use. Invert can and hold 4 to 6 inches (10 to 15 cm) above surface to be marked. Press spray head to the side to actuate.
3. If clogging develops, turn spray head ¼ turn or remove and clean spray head slot. DO NOT stick a pin or other objects into can opening. With can and spray head pointed away from you, reinsert spray head with a gentle twisting motion.
4. To clean spray head for future use, turn can right side up and spray for 3 seconds.

 **WHITLAM**
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com