

### Features

- High-arch spout and 360-degree spout rotation offer superior clearance for filling pots and cleaning.
- UltraGlide engineered ceramic disc valves resist deterioration and mineral buildup, resulting in long-lasting, reliable performance.
- Two lever handles offer separate control of hot and cold water.
- Available in 7-3/4" (197 mm) swing spout reach.
- Matching finish sidespray.
- 1.8 gallons (6.8 L) per minute maximum flow rate at 60 psi (4.1 bar).
- Meets CalGreen requirements for kitchen faucets.

### Material

- Premium Metal construction.
- KOHLER finishes resist corrosion and tarnishing.

### Installation

- Four-hole installation.
- Handles pre-assembled on valves to simplify installation.

### Recommended Accessories

K-1893



ADA

### Codes/Standards



ASME A112.18.1/CSA B125.1  
NSF 61  
NSF 372  
DOE - Energy Policy Act 1992  
ADA  
ICC/ANSI A117.1  
All applicable US Federal and State material regulations

### KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel

