

## Sump Pump Check Valves

- Flapper is nested in place to improve durability and longer life.
- Gasket-less design used on valve body.
- Injection molded ABS valve body is extremely tough and durable.
- Internal valve chamber uses a hydrodynamic design to reduce water turbulence and reduce noise.
- Silencer check valves completely eliminate hammering noises associated with pump cycling.
- Vertical or Horizontal

Made in U.S.A.

### Rubber Hose Coupling



- Valves come with all mounting hardware.

#### Standard



PART NO.	HOSE SIZE	LENGTH
29150	1-1/2"	7-3/4"
29126	1-1/4" x 1-1/2"	9-1/4"

#### Full Flow

PART NO.	HOSE SIZE	LENGTH
29120	2"	9-3/4"

#### "Silencer"

PART NO.	HOSE SIZE	LENGTH
29121	1-1/2"	12"
29122	2"	12-3/4"



### True Union Swing



- True Union coupling for easy swing-out during service/inspection
- Slip x Slip ends • O-Ring seals
- Ball valve/check valve combinations

#### "Silencer" True Union

PART NO.	HOSE SIZE	LENGTH
29133	1-1/2"	9-1/2"
29134	2"	10-1/2"

#### "Silencer" Ball Valve / Check Combo

PART NO.	HOSE SIZE	LENGTH
29137	1-1/2"	14-1/8"
29138	2"	16-1/2"



### Compression Swing



- Fittings on both ends of valve for easy installation
- Ball valve/check valve combinations available
- No gluing required
- Heavy duty design

#### Compression

PART NO.	PIPE SIZE	LENGTH
29139	2"	9-1/4"