

**PowerPEX™**

**Sillcock**

Standard

- Large 2½" diameter mounting flange
- Lead-free solder joint



117X22

Item No	Connection	Pkg	Min Qty	Case Qty
117X22	½" F1807	B	25	25

**PowerPEX™**

**Frost-Proof\* Anti-Siphon Sillcock**

Standard

- Longer stem saves knuckle scrapes
- Thicker, easier turning handle
- Nickel-plated brass body with black metal handle

¼-Turn

- Extended tailpiece for ease of installation
- Extra-large mounting flange
- ANSI/NSF 61 listed
- Nickel-plated brass body



118X208P



119X210P

Item No	Connection	Length	Pkg	Min Qty	Case Qty
STANDARD					
118X204P	½" F1807	4"	B	5	5
118X206P	½" F1807	6"	B	5	5
118X208P	½" F1807	8"	B	5	5
118X210P	½" F1807	10"	B	5	5
118X212P	½" F1807	12"	B	5	5
118X212PPK	½" F1807	12"	C*	4	4
¼-TURN					
119X204P	½" F1807	4"	B	2	2
119X206P	½" F1807	6"	B	5	5
119X208P	½" F1807	8"	B	5	5
119X210P	½" F1807	10"	B	5	5
119X212P	½" F1807	12"	B	5	5

\* As with all frost-proof hydrants, removal of hose is required to ensure against freezing and breaking.



**PowerPEX™**

**Ice Maker Valve**

Straight and Tee

- Great for adding ¼" O.D. supply lines for ice makers or humidifiers
- Lead-free solder joint



637X920



637X9220

Item No	Connection	Pkg	Min Qty	Case Qty
STRAIGHT				
637X920	½" F1807 × ¼" O.D. compression	B	25	250
637X920PK2	½" F1807 × ¼" O.D. compression, 1/bag	C*	10	10
TEE				
637X9220	½" F1807 × ¼" O.D. compression	B	25	250
637X9220PK2	½" F1807 × ¼" O.D. compression, 1/bag	C*	10	10