SPECIFICATIONS

20ga. recessed box (18ga. surface mounted box); 22ga. tubular steel door with 20ga. frame and a continuous steel hinge. All components are powdercoated with an electrostatically-applied, thermallyfused, recoatable white polyester finish. All glass door styles provided with clear tempered safety glass. Wall mounting and size of cabinet as selected by model

REGULARLY FURNISHED

1810 Series - For use with 2-1/2" Fire Department Valve

*Note: To accommodate a single. 2-1/2" fire department valve with cap chain. For Valve, cap & chain and reducer, specify 10" deep box

1830 Series - For use with 2-1/2" Pressure Regulating Valve

*Note: To accommodate a single, 2-1/2" 4005-4038 pressure regulating fire department valve with cap and chain. This cabinet may be used with other valves when spanner clearance is a factor, or when a 2-1/2" x 1-1/2" adapter is required.

MODEL SELECTION

☐ 1810 Recessed										
☐ 1811 Trimless										
☐ 1812 Semi-Recessed										
☐ 1815 Surface										
☐ 1830 Recessed										
☐ 1831 Trimless										
☐ 1832 Semi-Recessed										
☐ 1835 Surface										
PRODUCT OPTIONS										
DOOR AND FRAME MATERIAL:										
] -AL ALUMINUM: Clear Anodized Finish] -SS STAINLESS STEEL: 304 w/ #4 Finish] -PB BRASS: Polished Finish] -BZ BRONZE: Call for Options										
FINISHES:										
□ -ALLIMINUM: Duranodic Finish										



PRODUCT OPTIONS (cont.)

CABINET MODIFICATIONS:

□ -DANA TYPE: Frameless Concealed Hinge and Handle Construction (recessed cabinet only)

-DP **Duplex Cabinet**

-10 10" Deep Box (1810-1812 models only)

DOOR STYLES:

□ -A	Full Glass, w/ Tempered Safety Glass
□ -B	Break-Glass, w/ Lock & Break Rite® Handle
🔲 -D	Duo-Panel w/ Tempered Safety Glass
🔲 -DV	Duo-Vertical Panel w/ Tempered Safety Glass
🔲 -DVL	Duo-Vertical Panel w/ Lock, TSG & Break Rite®
	Handle
□ -E	Tempered Safety Glass (25 sq. in.) w/ Break
	Rite® Handle
□ -F	Flush Solid Metal
🔲 -FS	Flush Solid Metal w/ lock
□ -J	Insert Panel
(Specify)	Optional inserts for glass-style doors

**NOTE: DOOR STYLES -A, -D, -DV, -F, & -J PROVIDED w/ LEVER HANDLE/CAM LATCH

**NOTE: ALL GLASS DOOR STYLES PROVIDED WITH CLEAR TEMPERED SAFETY GLASS IN COMPLIANCE WITH ANSI Z97-1-1984


Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

☐ Light ☐ Medium

☐ 304 w/ #6 Dull Satin

□ -RED: Powder Coat

-CUSTOMER COLORS



-STAINLESS STEEL: Finish as Specified



☐ 304 w/ #8 Mirror

Dark



(Specify)







POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890


Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473


1810 SERIES Date: 03/14/17


MODEL DIMENSIONS


Model No.	Wall Mounting	Inside Box Dimensions			Overall Frame		Wall Opening Required			Trim	Inlet Location				ADA
		К	L	М	N	0	W I D T H	H E I G H T	D E P T H	т	w	x	Y	z	Ė
1810	Reccessed	18	18	*8	21-3/4	21-3/4	19	19	*8-1/2	5/8	4	4	4	9	Yes
1811	Trimless	18	18	*8-3/4	21	21	19	19	*9-1/4	-	4	4	4	9	Yes
1812	Semi-Reccessed	18	18	*8	21-1/2	21-1/2	19	19	*6-1/2	2	4	4	4	9	Yes
1815	Surface	20	20	9-1/4	-	-	-	-	-	-	-	-	-	-	No
1830	Reccessed	24	24	10	27-3/4	27-3/4	25	25	10-1/2	5/8	12	4-3/4	-	-	Yes
1831	Trimless	24	24	10-3/4	27	27	25	25	11-1/4	-	12	4-3/4		-	Yes
1832	Semi-Reccessed	24	24	10	27-3/4	27-3/4	25	25	8-1/2	2	12	4-3/4	-	-	Yes
1835	Surface	26	26	11-1/4	-	-	-	-	-	-	-	-	-	-	No

NOTE: * Add 2" for (-10 Option)









Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer-Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

1810 SERIES

Date: 03/14/17



NFPA











POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473

www.potterroemer.com