

Single Aluminum

- **Quick & Easy Installation** - Modular design with a maximum of 4 tongue and groove sections.
- **Easy Access** - Lightweight removable doors can easily be removed by one person.
- **Peace of Mind** - ASSE 1060 certification ensures that requirements for structural strength, drainage capacity, material construction, equipment access, and functional design are met.
- **Superior Freeze Protection** - Insulation will not sag or delaminate from the walls due to the strong chemical bond between the aluminum and insulation. Wall-mounted heaters are installed above the discharge point to provide better long-term performance and safety.
- **Finish Options** - Stucco embossed aluminum is standard. Also available in a smooth mill finish aluminum or optional colors (see page 49 for details).



For unheated units, replace the “H” in the part# with an “L”. Pad size=inside Dimensions + 12”.

Catalog Part Number	Model Number	Inside Width (in)	Inside Length (in)	Inside Height (in)	Heater(s)	Sections	Weight #
HA026070055	HB3E-AL	26	70	55	(1) 1500W	2	152
HA026083055	HB3ES-AL	26	83	55	(1) 1500W	2	168
HA032090050	HB4N	32	90	50	(1) 1900W	2	178
HA032090057	HB4E	32	90	57	(1) 1900W	2	192
HA032102050	HB4NS	32	102	50	(1) 1900W	2	192
HA032102057	HB4ES	32	102	57	(1) 1900W	2	209
HA033053044	HB4000AN	33	53	44	(1) 1000W	2	121
HA036105053	HB6N	36	105	53	(1) 1900W	2	209
HA036105064	HB6E	36	105	64	(2) 1500W	2	238
HA036105080	HB6ET	36	105	80	(2) 1500W	2	278
HA036125053	HB6NS	36	125	53	(2) 1500W	4	266
HA036125064	HB6ES	36	125	64	(2) 1500W	4	299
HA039062046	HB6000AN	39	62	46	(1) 1500W	2	155
HA040118058	HB8N	40	118	58	(2) 1500W	2	266
HA040118074	HB8E	40	118	74	(2) 1500W	2	312
HA040142058	HB8NS	40	142	58	(2) 1500W	4	311
HA040142074	HB8ES	40	142	74	(2) 1900W	4	363
HA042142065	HB10N	42	142	65	(2) 1500W	4	342
HA042142085	HB10E	42	142	85	(2) 1900W	4	404
HA042172065	HB10NS	42	172	65	(2) 1900W	4	392
HA042172085	HB10ES	42	172	85	(2) 1900W	4	469
HA044053044	HB4000AE	44	53	44	(1) 1000W	2	147
HA045072052	HB8000AN	45	72	52	(2) 1000W	2	197
HA045072060	HB8000ANT	45	72	60	(2) 1000W	2	235
HA047047049	HB6FE-AL	47	47	49	(1) 1500W	2	149
HA053053056	HB8FE-AL	53	53	56	(1) 1500W	2	183
HA053062046	HB6000AE	53	62	46	(1) 1500W	2	175
HA054062056	HB10FE-AL	54	62	56	(1) 1900W	2	197
HA065072052	HB8000AE	65	72	52	(2) 1000W	2	224
HA065072060	HB8000AET	65	72	60	(2) 1000W	2	244

For unheated units, replace the “H” in the part# with an “L”. Pad size=inside Dimensions + 12”.

