



UPC Code: 078477391990

Country Of Origin: Mexico

TDR20-I

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Ivory

Technical Information

Warranty Horsepower Rating: 1 HP Warranty: 10 Years

AC Horsepower Rating Amperage: 20 A

Dielectric Voltage: Withstands 3000 V minimum

Grounding: Self-Grounding Horsepower Rating: 1 HP

Pole: 2

Temperature Rise: Max 30 °C temperature rise at full rated current Voltage: 125 VAC

Wire: 3

Electrical Specifications

Amperage: 20 A Dielectric Voltage: Withstands 3000 V minimum

Flammability: Rated V-0 per UL 94

Grounding: Self-Grounding Operating Temperature: -40°C to 75°C

Pole: 2

Temperature Rise: Max 30 °C temperature rise at full rated current Voltage: 125 VAC

Wire: 3

Environmental Specifications Body Material: PBT Polyester Blend Color: Ivory

Face Material: PBT Polyester Blend Flammability: Rated V-0 per UL 94

Ground Clips: Brass Ground Contacts: 0.030" Brass

Grounding Screw: #8 Hex Head, Triple-Drive Brass

Line Contacts: 0.030" Phosphor Bronze Mounting Screws: Triple-Drive Plated Steel

Operating Temperature: -40°C to 75°C Shutter Mechanism: Acetal

Strap Material: Steel (Galvanized G60) Terminal Clamps: Brass

Terminal Screws: #8 Triple-Drive Brass

Material Specifications

Body Material: PBT Polyester Blend Face Material: PBT Polyester Blend Ground Clips: Brass Line Contacts: 0.030" Phosphor Bronze Mounting Screws: Triple-Drive Plated Steel

Product ID: Ratings are permanently marked on device

Shutter Mechanism: Acetal

Strap Material: Steel (Galvanized G60) Terminal Accom.: #14 AWG - #10 AWG

Terminal Clamps: Brass Terminal ID: Brass - Hot, Silver -Neutral, Green - Ground,

Terminal Screws: #8 Triple-Drive Brass Termination: Back or Side Wire Wire Type: Stranded or Solid

Mechanical Specifications

Brand: Decora Plus Color: Ivory

Color / Feature: Ivorv

Device Type: Duplex Receptacle Outlet

Feature 2: Tamper-Resistant

Feature 4: Smooth Face

Grade: Heavy-Duty Industrial Specification Grade

Product ID: Ratings are permanently marked on device

Terminal Accom.: #14 AWG - #10 AWG

Terminal ID: Brass - Hot, Silver - Neutral, Green - Ground,

Termination: Back or Side Wire Wire Type: Stranded or Solid

Product Features ANSI: C-73

Applicable Standards: UL 498, Fed Spec W-C-596, CSA C22.2. No. 42 Brand: Decora Plus

Certification/Listing: cULus, NOM-ANCE

Color: Ivory

Color / Feature: Ivory

Device Type: Duplex Receptacle Outlet Feature 2: Tamper-Resistant Feature 4: Smooth Face Grade: Heavy-Duty Industrial Specification Grade

RoHS: RoHS Compliant

Standards & Certifications
ANSI: C-73

Ground Contacts: 0.030" Brass Grounding Screw: #8 Hex Head, Triple-Drive Brass Applicable Standards: UL 498, Fed Spec W-C-596, CSA C22.2. No. 42 Certification/Listing: cULus, NOM-ANCE RoHS: RoHS Compliant

Patents*	
CA2483480	US6743029
CA2621644	US7355117
CA2624409	US7820909
CA2677283	US7868719
CN200880004760.2	US8242362
MX257790	US8684771
MX321216	

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

