
PFWR

Heavy Duty Wax Bowl Ring

Product Features

- 100% pure petroleum wax gasket for setting any floor type closet bowl
- Wax Bowl Ring fits all floor-type toilet bowls with 3” or 4” waste lines
- 48 per pack
- 25 lbs. carton weight



PFWR

Physical/Chemical Properties

Specific Gravity	0.82 – 0.86
Appearance	Golden Wax
Shelf Life	1 year from manufacture
Melting Point	150° F – 160° F

Directions for Use

Wax Ring works best at room temperature to ensure proper flow of wax. All surfaces must be dry and free of putty, scale or other contaminated wax. Remove debris by scraping with putty knife or wire brush. Dust and dry all surfaces before installing gasket. Remove wax ring from wrapping. Place wax firmly over the horn of the outlet on the toilet bowl and set into place over closet bolts, using body weight to compress gasket. Gently twist bowl to spread wax. Tighten flange bolts carefully to prevent cracking or chipping the toilet bowl.

Precautions

Read all cautions and directions carefully before using this product. Make sure water supply is shut off before beginning installation. For use on floor closet bowls only. DO NOT INSTALL ON WET SURFACES. Keep away from direct sunlight to prevent darkening. Do not store near extreme heat. KEEP OUT OF REACH OF CHILDREN.

Common Applications

PROFLO Heavy Duty Wax Bowl Ring provides a permanent, sanitary, gas and watertight seal on most types of water closets. Wax Bowl Ring will not dry out, harden or deteriorate.

Ingredients

Petrolatum (Non-Hazardous)
When used for the intended end use application, this product is considered an “article” as defined in OSHA 29 CFR 1910.1200(c).

Approvals and Listings

Meets Federal Specification TT-P-1536A.

© 2008 Wolseley