



MAXI-VENT® Air Admittance Valve

Manufacturer: **Studor®**, Inc.

Connection Size: **3" or 4"**

Model #: **MAXI-VENT®**

Item #: **20302**

General:

An air admittance valve shall be acceptable as a vent termination for any individual vent, common vent, circuit vent, loop vent, island fixture vent, vent stack or stack vent that is provided to prevent siphonage of a fixture trap. An air admittance valve can be used as an alternative to extending a vent through the roof (or sidewall) to the open atmosphere.

Location:

- A. The MAXI-VENT shall be located a minimum of 4" above horizontal branch drain or fixture drain being vented and 6" above the flood level of the highest fixture for stack venting.
- B. Each valve should be installed in an accessible location.

Installation:

- A. The valve should be connected to the piping in accordance with the manufacturer's installation instructions.
- B. The valve should be installed in the vertical, upright position after rough-in and pressure testing of the DWV system.
- C. A minimum of one vent shall extend to the open atmosphere for every building drainage system.
- D. The valve should not be installed in a non-neutralized special (chemical) waste system or in supply and return air plenums.
- E. The valve may be installed on sewer ejectors, if installed according to engineer design and prior local code approval.
- F. For installation in areas with temperature range between -40 and 150° F.

Features:

- A. Screening on the inside and outside of the valve to protect the sealing membrane from insects and debris.
- B. Protective cover for additional insulation against extreme temperatures.
- C. Ability to divert condensation away from sealing membrane.
- D. Limited lifetime warranty for replacement of defective valves.

Materials:

- A. Styrofoam cover
- B. ABS (acrylonitrile butadiene styrene) valve with silicone membrane
- C. Rubber connector

Performance Standards:

ANSI/ASSE 1051 A&B —2009 single fixture and branch type AAVs

ANSI/ASSE 1050—2009 stack type AAVs

NSF Standard 14—2009 Plastics Piping System and Components

Code Compliance:

- International Plumbing Code (IPC)
- International Residential Code (IRC)
- Uniform Plumbing Code (UPC Section 301.2 Alternative Materials and Methods)
- National Standard Plumbing Code (NSPC) - Appendix "E"
- National Plumbing Code of Canada (NPC)

Listings:



Horizontal Branch Size	Max DFUs
3"	20
4"	160
Stack Size	Max DFUs
3"	72
4"	500

