



Wheeler Rex Model 466000 Hydrostatic Test Pump Specifications

DIMENSIONS:	28" (70cm) L x 24" (60cm) W x 35" (87.5cm) H
WEIGHT:	136 lbs. 62 kg
PUMP:	Triple diaphragm: Positive displacement Ports: 1" Inlet; ¾" NPT outlet Capacity: 15gpm, 57lpm Pressure: 100-300psi Operating Speed: 550rpm Lubrication: Pump: 23oz of 40W Hyd Oil, Gear case: 16oz of 80/90W Gear Oil Shaft Size: 1"
ENGINE:	5.5hp Honda 4 cycle, gasoline with 6-1 gear reduction
CONTROL:	Adjustable pressure relief valve
PULSATION CONTROL:	Pulsation dampener
GAUGE:	Glycerin filled, 0-600psi, 0-42kg
DISCHARGE HOSE:	¾" x 10' (3m) 1000psi rated
INTAKE HOSE:	1" x 10' (3m)

FEATURES



- ✓ Able to handle up to 10% chlorine solution
- ✓ Automatic and precise pressure build-up
- ✓ Isolates and maintains high pressure
- ✓ Automatic by-pass
- ✓ Constant volume
- ✓ Adjustable pressure control
- ✓ On two wheeled cart with pneumatic tires
- ✓ Inline strainer with stainless steel mesh filter and clear bowl