

4¹¹/₁₆" SQUARE OUTLET BOXES AND COVERS

Applications:

- For use with conduit
- For use in commercial and industrial applications, where larger sized conductor or wiring devices are needed and additional volume is required
- Can be ceiling mounted to be used as a junction box or to mount lighting fixtures
- Available in red for fire alarm applications

Features:

- Ideal for exposed work applications, providing an easy method for the installation of electrical devices (switches, receptacles, fans, lights, etc.)
- Raised ground screw location in the welded boxes saves time in installation
- Concentric knockouts have a 1/2" and 3/4" knockout in the same location for customer flexibility
- Knockouts are suitable for use without a bonding jumper in circuits above or below 250 volts
- Available in two depths for differing cubic capacity requirements
- Welded or drawn construction to match customer preference
- Extensive cover offering to meet various customer applications and needs



Steel Boxes

Certifications and Compliances:

- UL Listed

4¹¹/₁₆" SQUARE OUTLET BOXES – 29.5 CUBIC INCH CAPACITY

1 1/2" DEEP WITH CONDUIT KOs

UL LISTED



TP523



TP548



TP549

		KNOCKOUTS			
Cat. #	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
29.5 CUBIC INCH CAPACITY					
TP523	Welded	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	99
TP523PF†	Welded	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	99
TP548	Drawn	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	84
TP549	Drawn	6 – 1/2", 6 – 1/2" & 3/4" C	3 – 1/2", 2 – 3/4"	25	84

†TP catalog numbers ending in PF includes ground screw with pigtail lead

Steel Square Boxes



4¹¹/₁₆" SQUARE OUTLET BOXES – 42.0 AND 44.0 CUBIC INCH CAPACITY

2¹/₈" DEEP WITH CONDUIT KOs

UL LISTED

Steel Boxes



TP563



TP554
TP842*



TP556
TP832*



TP556RED



TP558
TP835*



TP560
TP836*



TP562



TP557



TP521



TP525

			KNOCKOUTS			
Cat. #	Description	Brackets	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
42.0 CUBIC INCH CAPACITY						
TP563	Drawn	—	6 – 1/2", 6 – 1/2" & 3/4" C	3 – 1/2", 2 – 3/4"	25	104
TP554	Drawn	—	8 – 3/4"	3 – 1/2", 2 – 3/4"	25	104
TP556	Drawn	—	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	104
TP556PF†	Drawn	—	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	104
TP556RED	Drawn	—	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	104
TP558	Drawn	—	4 – 3/4", 4 – 1"	3 – 1/2", 2 – 3/4"	25	104
TP560	Drawn	—	8 – 1"	3 – 1/2", 2 – 3/4"	25	104
TP562‡	Drawn	—	4 – 1 1/4"	3 – 1/2", 2 – 3/4"	25	104
TP557	Drawn	"VS"	4 – 1/2", 5 – 1/2" & 3/4" C	3 – 1/2", 2 – 3/4"	25	120
44.0 CUBIC INCH CAPACITY						
TP521	Welded	—	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	115
TP521PF†	Welded	—	12 – 1/2" & 3/4" C	2 – 1/2", 2 – 3/4"	25	115
TP525**	Welded	—	12 – 1/2" & 3/4" E	2 – 1/2", 2 – 1/2", 3/4" E	25	115
Air Plenum						
TP835*		—	4 – 3/4", 4 – 1"	3 – 1/2", 2 – 3/4"	25	115
TP836*		—	8 – 1"	3 – 1/2", 2 – 3/4"	25	115
TP842*		—	12 – 3/4"	3 – 1/2", 2 – 3/4"	25	115
TP832*		—	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	115

*For Air Plenum (No Mounting Holes) - Not UL Listed

**Raised ground bump contains holes for 2 ground screws

†TP catalog numbers ending in PF includes ground screw with pigtail lead

‡ Not UL Listed