

FRONT-FIT™ REMODELING SHOWERS

WR 534 FF

Unit Outside Dimension: 60" x 34" x 78"

Inside Dimension: TBD

Front Outside Threshold height: 3"

Inside dam height: 1 ½"

Door Opening: 56 ¾" x 76"

Shipping weight: starting at 160 lbs.



Features:

- NO seat for Spacious 34" shower
- Low 3" front outside threshold for easy entry
- 1 ½" inside dam to contain water
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard
- Flat walls for easy grab bar positioning at 34" (ADA height) above the floor and for vertical grab bar on either side wall - must order as H 534 for grab bar reinforcement

Options:

See Page 34 for reinforced unit and page 66 for Accessory Options.



WR 350 FF (RH) - Left Seat WR 351 FF (LH) - Right Seat

Unit Dimensions: 48" x 36" x 81 ½"

Inside Shower Dimensions: 41" x 29"

Door Opening: 38 ½" x 73 ½"

Front Threshold Height: 6"

Shipping Weight: 130 lbs.



Features:

- Front-Fit remodeling system for easy installation
- Largest integral contoured seat in its class
- 3-piece remodeler, will fit through any 24" door
- Extra height for comfort & safety (keeps water in the shower and off the floor)
- Reinforced pillars for shower door or curtain rod support
- Elevated corner shelf
- Textured floor - meets and exceeds ASTM F-462 slip resistance standard
- Boot Print balsa wood base

Options:

T-85 dome, dome light, custom backing for additional grab bars, and above-floor rough-in

