




Schedule 40 Fittings Technical
Schedule 40 Fittings Dimensions & Information

Coupling - Eccentric Reducer

(Continued)

Socket x Socket



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
429-529FE ^{3*}	6X2-1/2	19- 7/16	7- 1/8	3- 1/4	14- 3/16	3.76
429-530FE ^{2*}	6X3	16- 5/16	7- 1/8	3-15/16	10-13/16	3.16
429-532E	6X4	8-31/32	7- 9/32	5- 1/32	3-15/16	2.90
429-532FE ⁺	6X4	11- 1/8	7- 1/8	5	5- 5/8	2.27
429-533FE ⁺	6X5	10- 5/8	7- 1/8	6- 1/16	4- 3/8	2.84
429-578FE ^{3*}	8X2	27- 1/8	9- 3/16	2-11/16	21- 1/2	9.64
429-580FE ^{3*}	8X3	25- 5/16	9- 3/16	3-15/16	18-13/16	7.18
429-582FE ^{2*}	8X4	19- 5/8	9- 3/16	5	13- 3/8	8.21
429-583FE ^{2*}	8X5	15- 5/8	9- 3/16	6- 1/16	12- 3/8	6.77
429-585FE ⁺	8X6	14- 3/8	9- 3/16	7- 3/16	6- 7/8	4.85
429-624FE ^{2*}	10X4	22- 3/8	11- 3/8	5	15- 1/8	10.13
429-625FE ^{2*}	10X5	22-3/8	11-3/8	6-1/16	14-1/8	9.33
429-626FE ⁺	10X6	17- 1/8	11- 3/8	7- 1/4	8- 5/8	7.48
429-628FE ⁺	10X8	16-11/16	11- 3/8	9- 1/4	7-3/16	8.48
429-664FE ^{3*}	12X4	32- 3/8	13- 1/2	5	24- 1/8	20.15
429-666FE ^{2*}	12X6	27- 1/8	13- 1/2	7- 1/4	17- 5/8	16.79
429-668FE ^{2*}	12X8	26-11/16	13- 1/2	9- 1/4	16-3/16	18.12
429-670FE ⁺	12X10	18- 3/8	13- 1/2	11- 1/2	6- 7/8	13.53
429-696FE ^{2*}	14X6	31- 3/8	15	7- 1/4	21- 1/8	26.14
429-698FE ^{2*}	14X8	30-15/16	15	9- 1/4	19-11/16	26.76
429-700FE ⁺	14X10	22- 3/4	15	11- 3/4	10- 1/2	23.23
429-702FE ⁺	14X12	19	15	13- 3/4	5- 3/4	21.29
429-756FE ^{3*}	16X6	43- 5/8	17	7- 1/4	32- 3/8	42.00
429-758FE ^{3*}	16X8	42-3/16	17	9- 1/4	30-15/16	42.02
429-760FE ^{2*}	16X10	34- 7/8	17	11- 1/2	21- 5/8	38.22
429-762FE ^{1*}	16X12	26- 1/2	17	13- 3/4	12- 1/4	30.12
429-764FE ⁺	16X14	21-3/4	16- 7/8	14- 7/8	6- 3/4	24.61
429-786FE ^{4*}	18X6	56	19	7- 1/4	43- 3/4	71.11
429-788FE ^{4*}	18X8	55-9/16	19	9- 1/4	42-5/16	70.92
429-790FE ^{3*}	18X10	47- 1/4	19	11- 1/2	33	65.31
429-792FE ^{2*}	18X12	38- 7/8	19	13- 3/4	23- 5/8	55.50
429-794FE ^{2*}	18X14	34- 1/8	19	14- 7/8	18- 1/8	49.03
429-796FE ⁺	18X16	25	19	17	8	38.72

* Fabricated