Installation Instructions

High Efficiency Flush Valve Bowl, Wall Mount

Tools and Materials

Level; Putty Knife; Screwdriver; Tape Measure; Silicon Caulk; Adjustable Wrench; Flush Valve; Closet Carrier Support

1. Follow closet carrier support installation instructions. Confirm the carrier support studs extend a minimuim of 1-7/8" (48mm) from the finished wall.

2. Place back up nuts on top left and bottom two bolts. Adjust the nuts so the frontface of the nuts are flush with the finished wall. Use a hack saw blade to gauge recommended tolerances of 1/16" (1.5mm) gap between the fixture and the wall surface.

3. Adjust the waste horn so that 5/16" (7mm) extends past the finished wall

4. Follow the manufactutrers closet carrier support recommendations setting of the closet outlet connection

5. Use a felt or rubber gasket, (wax ring not recommended) on closet outlet.

6. With a helper, carefully mount the bowl onto the carrier studs using fiber washers and cap nuts. Hand tighten . Do not apply top right fiber washer until the other three nuts are firmly tightened. Hand tighten top right cap nut. Apply silicon sealant between bowl and finished wall.

Flushometer Valve Installation

NOTE: For proper operation product requires 30 psi working line pressure. Use the flush valve manufacturer's installation instructions for installing the valve and for adjusting the water usage for 1.28 gpf.

Care & Maintenance

Do not use abrasive powered or liquid cleaners which can damage the product surface.

Caution

Product is Fragile. To avoid breakage and possible injury handle with care!

Warranty

WHAT IS COVERED?
Ferguson Enterprises, Inc. "Ferguson" or the "Company" warrants its products to be free from defects in material and workmanship under normal use and service FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF INSTALLATION.

WHAT IS NOT COVERED?
The warranty set forth in paragraph 1 does not cover installation or any other labor charges and does not apply to products which have been damaged as a result of any accident, abuse, improper installation or maintenance, or modification of original plumbing product. The warranty of such products is limited to the warranty extended to Ferguson by the product manufacturer. Finally, FERGUSON SHALL NOT BE RESPONSIBLE OR LIABLE FOR ANY FAILURE OR DAMAGE TO THIS PRODUCT OR ANY COMPONENT THEREOF CAUSED BY THE USE OF ABRASIVE CLEANERS.

HOW TO OBTAIN WARRANTY SERVICE

US Customers:
The purchaser should contact their local Ferguson location, installing contractor or builder from whom the product was purchased. To find you nearest Ferguson location please visit www.ferguson.com and enter in your address into the Find a Location field.

Canadian Customers:
The purchaser should contact their local Wolseley Canada location, installing contractor or builder from whom the product was purchased. To find your nearest Wolseley Canada location please visit www.wolseleyinc.ca, then click on Find a Location and enter your address into the location field.

PROFLO is a registered trademark of Ferguson Enterprises, Inc.

LIMITATIONS OF IMPLIED WARRANTY AND DISCLAIMER OF CONSEQUENTIAL OR INCIDENTAL DAMAGES FERGUSON DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES AND DISCLAIMS ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AS SET FORTH ABOVE. IMPLIED WARRANTIES OF THE PRODUCTS AND PRODUCT COMPONENTS SET FORTH IN PARAGRAPH 1 ABOVE ARE LIMITED TO THE DURATIONS OF THE RESPECTIVE WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

©2008 Wolseley