

SPECIFICATIONS

FIGURE 7824
STRUT ACCESSORIES



TOP SPRING CHANNEL NUT

FNW Channel Nuts feature serrated grooves that fit onto strut channels, securing threaded rod and other hardware to strut channel.

FEATURES


- Comes stock with an electro-galvanized finish
- For all channel sizes except as noted on spec table

PRODUCT SPECIFICATIONS

Material Specifications and Finishes

Carbon Steel – ASTM A1011-00 SS GR 33 or ASTM A1011-00CS Type B

Z: Electro-galvanized (standard finish). Electroplating deposits zinc on the surface of the steel by electrolysis from a bath of zinc salts. Recommended for relatively dry indoor use. This is the standard coating for most FNW products. Thickness of applied zinc is between 0.2 mils to 0.5 mils [5.1 µm to 12.7 µm]. Coatings on FNW Z products meet ASTM B633 SC1 Type III.



Item #	Thread Size		Thickness		Weight	
	in.	mm	in.	mm	lbs	kg
FNW7824Z0025	1/4	8	0.25	6.3	0.093	0.042
FNW7824Z0037	3/8	10	0.37	9.4	0.093	0.042
FNW7824Z0050*	1/2	12	0.50	12.7	0.101	0.046

*Cannot be used with 13/16" & 1" channel