

Protect

Provides a minimum 1" offset from mounting surface, protecting tube from sheetrock installers.

Strong

I-beam design on stem stands up to the demands of the job site and the locking finger holds the tube securely in place.

Quiet

Reduces noise associated with expansion and contraction of tube, and doesn't allow the tube to come into contact with the stud or joist.

Compatible

For use with $\frac{1}{2}$ " or $\frac{3}{4}$ " CTS tube (copper, PEX, CPVC).



www.siouxchief.com



Supply Drainage Support

TAKE THE FIELD.

Moving the tube away from the mounting surface reduces chances of other trades or homeowners penetrating water supply lines causing potential leaks. Once PEX tubing has been penetrated with a nail or screw, it may take weeks or months for rust to develop, concealing a leak behind the wall.



Nails or screws can pierce the tubing causing leaks behind the wall.



Designed with a 1" offset from the structure, placing the tube away from the mounting surface.



The unique base fastens to any flat surface or on the engineered wood joist flange.



Reduce costs by installing <u>one</u> hanger for parallel tube runs.

>>> Buying Information						
	ITEM NO.	DESCRIPTION	MIN QTY	CASE QTY		
Single Offset						
I	552-A2	1/2" CTS	50	500		
	552-A3	³ ⁄4" CTS	50	500		
Twin Offset	Twin Offset					
T	552-B22	1⁄2" CTS x 1⁄2" CTS	50	500		
	552-B23	1⁄2" CTS x 3⁄4" CTS	50	500		
	552-B33	3⁄4" CTS x 3⁄4" CTS	50	500		
Stacked Offset						
	552-C22	1⁄2" CTS x 1⁄2" CTS	50	500		
	552-C23	1⁄2" CTS x 3⁄4" CTS	50	500		
	552-C33	³ ⁄ ₄ " CTS x ³ ⁄ ₄ " CTS	50	500		
10						

>> Material Specifications				
MATERIAL	U.V. resistant HDPE			
NAIL	1-5/8" or 2-1/2", zinc-plated, ring shank			
IMPACT RESISTANCE	to 0°F (-18°C)			
MAXIMUM TEMPERATURE	160°F (71°C) continuous			

Note:

- Totem hangers are not suspension hangers. Sioux Chief does NOT recommend installing upside down.
- Ring-shank nails are provided with all models, but are not pre-installed

14940 Thunderbird Road Kansas City, Missouri 64147 P 1.800.821.3944 F 1.800.758.5950 DISTRIBUTED BY



