

SPEAKMAN® SM-3090-ADA

Versatile™ Pressure Balance Handicap Shower/Tub Combination

FEATURES:

- Includes Sentinel Mark II® concealed anti-scald balanced pressure shower valve and handheld spray combination.
- Chrome plated brass wall plate with metal index.
- Chrome plated brass lever handle.
- Independent center sleeve allows up to 1 in. of rough-in variation.
- Adjustable temperature limit stop. Brass body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- Four port valve with 1/2 in. female copper sweat inlets and shower outlet (tub outlet 1/2 NPT female).
- S-1556 chrome plated tub spout diverter.
- In-line vacuum breaker.
- S-2500 shower arm and wall flange.
- VS-100-PC handshower with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum.
- Chrome 5' metal shower hose, 1/2 in. NPSF connectors.
- Swivel arm holder.
- 24 in. combination slide bar and grab bar, stainless steel and chrome.



FINISH:



PC

COMPLIANCE:

- ASSE 1016 & ASME 112.18.1/CSA B125.1 standards (SM-3000 valve)

OPTIONS:

Add suffix to model #

- Integral stops -IS
- Contractor Packs Available

WARRANTY:

- 5 year limited



NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified all inlets and outlets are 1/2" NPT female. 3. The location of the slide bar is optional, but restricted by the 69" hose length running from the shower arm bracket connection to hand shower and note #4. 4. See ICC/ANSI A117.1 standard and/or ADA accessibility guidelines for building and facilities (ADAAG) for installation locations and required dimensions based on your specific shower configuration.

DIMENSIONS:

