

Engineered Plastic (EP) Heating Manifold Single Section with Isolation Valve

Submittal Information
Revision B: April 19, 2011

Project Information

Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

Technical Data

Manifold:	PA66-GF30	Max. Test Pressure (24 h, ≤ 86°F) tested with water:	145 psi (10 bar)
Valve Insert, Handwheels:	POM	Max. Test Pressure (24 h, ≤ 70°F) tested with air:	100 psi (7 bar)
Metal Inserts:	Brass C38500	Max. Water Flow per Manifold:	0.97 l/s 15.4 gpm
Axel:	Stainless Steel	Cv Value Inlet/Outlet Valves:	1.35
Spring:	Stainless Steel	Connection Dimensions:	R32
O-ring:	EPDM	Adaptable Actuators:	EP Heating Manifold, two-wire Actuator (A3030522); Thermal Actuator, four-wire (A3010522) with EP Heating Manifold Actuator Adaptor (A2671300)
Max. Operating Temperature and Pressure:	6 bar at 60°C	5 bar at 70°C	
	87 psi at 140°F	72 psi at 158°F	
	4 bar at 80°C	3 bar at 90°C	
	58 psi at 176°F	44 psi at 194°F	



Product Information and Application Use

The Engineered Plastic (EP) Heating Manifold Single Section with Isolation Valve (A2670001) adds additional loops to an EP Heating Manifold assembly for use in hydronic radiant heating and cooling systems. Use only propylene glycol in radiant systems with EP Heating Manifolds; never use ethylene glycol.

✓ Description	Part Number	Height	Width	Weight
EP Heating Manifold Single Section with Isolation Valve	A2670001	4.6"	2.0"	0.30 lbs.
EP Heating Manifold Isolation Valve Body, replacement part	A2670004	4.6"	2.0"	0.30 lbs.
EP Heating Manifold Valve Replacement Tool	A2670007	4.6"	2.0"	0.30 lbs.
EP Heating Manifold Replacement O-ring	A2670008	4.6"	2.0"	0.30 lbs.

Installation

Select the proper bracket spacing for the manifold and mount the bracket to the wall. Snap the manifold to the bracket. For additional information, refer to the instruction sheet. **Note:** Use only propylene glycol in radiant heating and cooling systems with EP Heating Manifolds; never use methanol or ethylene glycol. Refer to the EP Heating Manifold Installation Guide for a complete chemicals list.

Standards/Codes/Listings

N/A

Related Applications

Radiant Heating and Cooling Systems
Snow and Ice Melting Systems
Permafrost Protection Systems
Turf Conditioning Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Road, Plaza 1, Suite 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca