

PEX COPPER CRIMP RING

Job Name _____
Location _____
Engineer _____
Contractor _____
Tag _____ PO# _____

Specifications

- Manufactured to the highest industry standards, Jones Stephens' F1807 crimp fittings provide precise, leak-free connections. The secure and reliable crimp fitting method provides full, immediate strength upon installation, with 360-degree uniform pressure. Approved for use with PEX piping.

Applications

- Commercial and residential non-potable water applications

Materials

- Copper



Dimensions and Product Offering

Part Code	Size	A - in (mm)	A - Tolerance \pm in (mm)	B - in (mm)	B - Tolerance \pm in (mm)	C - in (mm)	C - Tolerance \pm in (mm)
C76071	1/2	0.64 (13.06)	\pm 0.003 (0.08)	0.33 (8.26)	\pm 0.02 (0.51)	0.06 (1.42)	\pm 0.003 (0.08)
C76072	3/4	0.89 (22.56)	\pm 0.003 (0.08)	0.33 (8.26)	\pm 0.02 (0.51)	0.06 (1.42)	\pm 0.003 (0.08)
C76073	1	1.15 (29.21)	\pm 0.003 (0.08)	0.37 (9.40)	\pm 0.02 (0.51)	0.05 (1.27)	\pm 0.003 (0.08)
C76108	1-1/4	1.39 (35.30)	\pm 0.003 (0.08)	0.55 (13.97)	\pm 0.02 (0.51)	0.06 (1.42)	\pm 0.003 (0.08)
C76109	1-1/2	1.65 (41.28)	\pm 0.003 (0.08)	0.65 (16.51)	\pm 0.02 (0.51)	0.065 (1.65)	\pm 0.003 (0.08)
C76110	2	2.16 (54.86)	\pm 0.003 (0.08)	0.75 (19.05)	\pm 0.02 (0.51)	0.07 (1.78)	\pm 0.003 (0.08)

Certifications/Listings/Approvals

- ASTM F1807
- ASTM F877
- CSA B137.5
- NSF/ANSI 14

