Oatey®
4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

101 PS SERIES SOLVENT WELD SHOWER DRAIN

TECHNICAL SPECIFICATION: Oatey Solvent Weld Shower Drains are designed for use with preformed shower stall bases. The drain seals to the base with fiber and rubber washers. 2" Schedule 40 DWV pipe solvent welds to the drain base. Drain top accommodates 4-¼" Universal Snap-Tite Strainers available in a variety of designer finishes.

PHYSICAL/CHEMICAL PROPERTIES

Material/Color ABS Plastic = Black
PVC Plastic = White

COMMON APPLICATIONS

Oatey Solvent Weld Shower Drains are designed for use with preformed shower stall bases. The drain seals to the base with fiber and rubber washers. 2" Schedule 40 DWV pipe solvent welds to the drain base. Drain top accommodates 4-¼" Universal Snap-Tite Strainers available in a variety of designer finishes.

INSTALLATION GUIDELINE

Rubber gasket is placed directly under the shower base, with the fiber gasket beneath it. The

- Made of PVC or ABS Plastic
- Easy to install
- Solvent welds over 2" Schedule 40 DWV pipe
- Available with 4-¼" Stainless Steel, White Plastic or UltraShine® PVD Polished Brass Snap-Tite Strainer

	PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
	42093	ABS Solvent Weld Shower Drain w/Stainless Steel Strainer	12	6 lbs.
	42097	PVC Solvent Weld Shower Drain w/Stainless Steel Strainer	12	6 lbs.
	42086	ABS Solvent Weld Shower Drain w/White Plastic Strainer	12	5 lbs.
	42089	PVC Solvent Weld Shower Drain w/White Plastic Strainer	12	8 lbs.
	42078	PVC Solvent Weld Shower Drain w/UltraShine® PVD Brass Strainer	12	6 lbs.