SPECIFICATION SUBMITTAL SHEET



[™] MAXI-FILTRA Air Admittance Valve

Manufacturer: **Studor®**, **Inc.** Connection Size: **3" or 4"**

Model #: MAXI-FILTRA™ Item #: 20297

Item #: 20700, Replacement Cartridge

General:

The MAXI-FILTRA is a two way vent, which filters air in both directions. It is designed for outdoor use only on septic tanks and lift stations. It is UV rated and comes with a replaceable carbon filter to eliminate bad odors.

Buildings connected to the main sewer can also benefit from the use of the MAXI-FILTRA, but Studor technical department must be contacted so that installation feasibility can be determined. The MAXI-FILTRA, as part of the complete STUDOR System[®] eliminates sewer gases from entering buildings or polluting the surrounding areas. It can also be retro-fitted in an existing plumbing system provided that all design and installation criteria are met.

Location:

A. The MAXI-FILTRA is for outdoor use only

Installation:

- A. Install filter after drainage and waste system has been roughed in and tested.
- B. Install valves in accessible locations to allow for filter cartridge replacement.
- C. Connect valves to piping in accordance with manufacturer's instructions.
- D. Do not install valves on chemical waste systems or in supply and return air plenums.
- E. The MAXI-FILTRA can be installed vertically or horizontally
- F. The MAXI-FILTRA contains a replaceable carbon filter cartridge which can last up to 2 years.

Features:

- A. UV inhibitor in resin compounds for exposure to sunlight
- B. Active Charcoal Filter replaceable cartridge

Materials:

- A. ABS (acrylonitrile butadiene styrene)
- B. Active Charcoal Filter replaceable cartridge
- C. Rubber connector





Replacement Cartridge

