

E-10 PREFILTER SYSTEM

System Part Number:

E-10 Prefilter System: EV9795-80

Everpure EC110 Prefilter Cartridge: EV9534-12



FEATURES • BENEFITS

- Filters out larger dirt and rust particles
- Durable slim bowl design makes for quick-change cartridge replacement
- Helps extend equipment life of primary filter cartridges
- Bowl design fits most 10" drop-in filter cartridges
- Tightly spun Everpure EC110 cartridge provides sediment reduction to 10 microns

APPLICATIONS


- For all foodservice applications requiring prefiltration
- High sediment areas

INSTALLATION TIPS

- Choose a mounting location suitable to support the full weight of the system when operating.
- Make sure to properly lubricate 0-ring prior to use.
- Use 3/4" water line (optional reducer bushings included).
- Install vertically with bowl hanging down.
- Allow 2 ½" (6.35 cm) clearance below the cartridge for easy cartridge replacement.

E-10 PREFILTER SYSTEM

EV9795-80



Specifications

Overall Dimensions

12.44" H x 5.16" W x 5.5" D (31.5 cm x 13.1 cm x 13.9 cm)

Operating Pressure

10 - 125 psi (0.7 - 8.6 bar), non-shock

Water Temperature

35 - 100°F (2 - 38°C)

Connections

Inlet Connection: 3/4" FNPT Outlet Connection: 3/4" FNPT

Operating Weight

6 lbs (2.7 kgs)

Shipping Weight

4 lbs (1.8 kgs)

Service Flow Rate

Maximum 4.0 gpm (15 Lpm)

Electrical Connection

None required

For Pentair Everpure Product Warranties visit: http://pentair.com/assets/foodservice-warranty

It is recommended that filter cartridges be replaced every six (6) months on a regular scheduled program, or when capacity is reached or if water pressure or flow to equipment becomes inadequate.

Always replace filter cartridges at least once per year.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.



