

S A F E T Y D A T A S H E E T

DP 3040 WHITE, WATER BASED VAPOR BARRIER COATING

Page: 1

===== SECTION I – PRODUCT AND COMPANY IDENTIFICATION =====


PRODUCT NAME: WHITE, WATER BASED VAPOR BARRIER COATING
PRODUCT CODE: DP 3040

MANUFACTURERS' NAME: DESIGN POLYMERICS

ADDRESS: 3301 W. Segerstrom Ave.
 Santa Ana, CA 92704

EMERGENCY PHONE: Chem-Tel: (800) 255-3924 (24 Hrs)
BUSINESS HOURS: 7:30am – 4:30pm PT
CONTRACT NUMBER: MIS0005056
REVISION DATE: March 16, 2018
INFORMATION PHONE: (714) 432-0600
REVISION #: 6
PREPARED BY: Technical Dept. Supersedes all previous
DOT HAZARD CLASS: Not Hazardous UN Number N/A
SHIPPING NAME: N/A Packing Group N/A

| HMIS | |
|---------------------|---|
| Health Hazard | 1 |
| Fire Hazard | 0 |
| Reactivity | 0 |
| Personal Protection | B |



===== SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION =====

| REPORTABLE COMPONENTS | CAS NUMBER | VAPOR PRESSURE mm Hg @ TEMP | WEIGHT PERCENT |
|-----------------------|------------|--------------------------------|-------------------|
| None | | | |

===== SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS =====

| CAS # | Trade secret Y/N | Chemical Name | Comment |
|-------------------|---------------------|---------------|---------|
| Proprietary Blend | YES | | |

===== SECTION IV – FIRST AID MEASURES =====

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Contact physician or emergency medical facility immediately.

SKIN: Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water for at least 15 minutes. Do not rub affected area. If irritation persists, get medical attention. Skin reaction may take 24 to 48 hours to develop. Wash contaminated clothing before reuse.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes while frequently lifting the upper and lower eyelids. If irritation persists, call a physician.

INGESTION: Do not induce vomiting. Contact physician or emergency medical facility immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN: Chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

===== SECTION V - FIRE-FIGHTING MEASURES =====

FLASH POINT: Not Applicable METHOD USED: Not Applicable
FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: The product will only burn after the water it contains is driven off. For dried film use water, foam, carbon dioxide or dry chemical.

S A F E T Y D A T A S H E E T

DP 3040 WHITE, WATER BASED VAPOR BARRIER COATING

Page: 2

SPECIAL FIRE FIGHTING PROCEDURES: When dried film burns, carbon dioxide (CO₂), carbon monoxide (CO), hydrogen chloride gas (HCl), and smoke are produced. Firefighters should wear self-contained breathing apparatus, especially in enclosed areas. Cool containers and minimize vapors with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high temperatures may explode or burst due to build-up of steam pressure.

===== SECTION VI – ACCIDENTAL RELEASE MEASURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike, contain, or absorb with inert absorbent material. Collect spilled material in a salvage container. Prevent spill from entering sewers, drains, streams, waterways, or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

===== SECTION VII – HANDLING AND STORAGE =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **DO NOT ALLOW TO FREEZE.** Store in a cool dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. Avoid inhalation of excess vapors, ingestion, and unnecessary, prolonged, or repeated contact with this and any other chemical. Change soiled work clothes frequently. Clean hands after handling. **KEEP OUT OF REACH OF CHILDREN.**

===== SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION =====

RESPIRATORY PROTECTION: Not required under normal conditions. Provide sufficient ventilation to maintain constant fresh air in workspace. If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

SKIN PROTECTION (PROTECTIVE GLOVES): Wear resistant gloves such as polyethylene.

EYE PROTECTION: Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious clothing. Eye wash station.

WORK / HYGENIC PRACTICES: Source of clean water should be available for flushing eyes and washing skin. Wash thoroughly after handling any chemicals, especially before eating, drinking, or smoking. Remove and launder contaminated clothing before reuse.

===== SECTION IX - PHYSICAL / CHEMICAL PROPERTIES =====

PHYSICAL FORM: mobile liquid

ODOR: Mild, sweet

SOLUBILITY IN WATER: Miscible

BOILING POINT: 212°F

FREEZING POINT: 32° F (0° C)

COATING V.O.C.: 0 g/l

COLOR: white

pH: 7.5-9.0

SPECIFIC GRAVITY (H₂O=1): 1.4-1.5

% VOLATILES BY WEIGHT: 30-35

VISCOSITY (cps): approx. 70,000-90,000

===== SECTION X – STABILITY AND REACTIVITY DATA =====

STABILITY: Stable at ambient temperatures.

CONDITIONS TO AVOID: Coagulation may occur after freezing, thawing, or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts, mineral acids (i.e. sulfuric, phosphoric, etc.) Strong oxidizing agents. Strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials on thermal decomposition including Carbon monoxide (CO), Carbon dioxide (CO₂), and various hydrocarbons. Under fire conditions, this product will release hydrogen chloride gas.

S A F E T Y D A T A S H E E T

DP 3040 WHITE, WATER BASED VAPOR BARRIER COATING

Page: 3

SECTION XI – TOXICOLOGICAL INFORMATION

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EYES: In direct contact, may cause irritation. SKIN: Prolonged and repeated contact with product may cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE: May cause irritation to skin and eyes, gastrointestinal irritation, nausea, and vomiting. CHRONIC: Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

SECTION XII – ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product

Environmental Fate: No environmental information found for this product

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines

SECTION XIV – TRANSPORT INFORMATION

| | | | |
|------------------|---------------|---------------|-----|
| DOT Hazard Class | Not Hazardous | UN Number | N/A |
| Shipping Name | N/A | Packing Group | N/A |

SECTION XV – REGULATORY INFORMATION

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Section 311/312 Categorizations (40 CFR 370): Immediate (Acute) Health Hazard.

Section 313 Information (40 CFR 372) – Toxic Chemicals List: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

| Component | CAS# | % by Weight |
|-----------|------|-------------|
| None | | |

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): None listed.

SECTION XVI – OTHER INFORMATION

| | |
|----------------------|----------------------|
| MSDS Creation Date: | April 14, 2015 |
| MSDS Revision Date: | March 16, 2018 |
| MSDS Revision Notes: | 16 section SDS |
| MSDS Author: | Technical Department |

S A F E T Y D A T A S H E E T

DP 3040 WHITE, WATER BASED VAPOR BARRIER COATING

Page: 4

Disclaimer: The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.